

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Fairchild Semiconductor](#)  
[H24A2](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



## PHOTOTRANSISTOR OPTOCOUPLEDERS

### H24A1 H24A2

#### PACKAGE DIMENSIONS



#### DESCRIPTION


The H24A series consists of a gallium arsenide infrared emitting diode coupled with a silicon phototransistor. The devices are housed in a low-cost plastic package with lead spacing compatible with a dual in-line package.

#### FEATURES

- 4-pin configuration
- Small package size and low cost
- UL recognized-file E51868

#### APPLICATIONS

- Digital logic inputs
- Microprocessor inputs
- Industrial controls



Equivalent Circuit

#### ABSOLUTE MAXIMUM RATINGS

##### TOTAL PACKAGE

Storage temperature	-55°C to 85°C
Operating temperature	-55°C to 85°C
Lead solder temperature	260°C for 5 sec

##### INPUT DIODE

Power dissipation (25°C ambient)	100 mW
Derate linearly (above 25°C)	1.67 mW/°C
Continuous forward current	60 mA
Reverse voltage	4 V

##### DETECTOR

Power dissipation (25°C ambient)	150 mW
Derate linearly (above 25°C)	2.5 mW/°C
V <sub>CEO</sub>	30 V
V <sub>ECO</sub>	6 V
Continuous forward current	100 mA



## PHOTOTRANSISTOR OPTOCOUPLEDERS

### ELECTRICAL CHARACTERISTICS (25°C Temperature Unless Otherwise Specified)

#### INDIVIDUAL COMPONENT CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
<b>INPUT DIODE</b>						
Forward voltage	$V_F$			1.7	V	$I_F = 60 \text{ mA}$
Reverse current	$I_R$			1	$\mu\text{A}$	$V_R = 3 \text{ V}$
Reverse breakdown voltage	$V_{(BR)R}$	4			V	$I_R = 10 \mu\text{A}$
Capacitance	$C_J$		30		pF	$V = 0, f = 1 \text{ MHz}$
<b>OUTPUT DETECTOR</b>						
Breakdown voltage Collector to emitter	$BV_{CEO}$	30			V	$I_C = 1 \text{ mA}, I_F = 0$
Breakdown voltage Emitter to Collector	$BV_{ECO}$	7			V	$I_C = 100 \mu\text{A}, I_F = 0$
Collector dark current	$I_{CEO}$		5	100	nA	$V_{CE} = 10 \text{ V}, I_F = 0$
Capacitance	$C_{CE}$		3.3		pF	$V_{CE} = 5 \text{ V}, f = 1 \text{ MHz}$

#### TRANSFER CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
<b>DC CURRENT TRANSFER RATIO</b>						
H24A1	$I_C$	10.0			mA	$I_F = 10 \text{ mA}, V_{CE} = 10 \text{ V}$
H24A2	$I_C$	2.0			mA	$I_F = 10 \text{ mA}, V_{CE} = 10 \text{ V}$
Saturation voltage	$V_{CE(SAT)}$		0.1	0.4	V	$I_F = 10 \text{ mA}, I_C = 0.5 \text{ mA}$
Turn-on time	$t_{on}$		9		$\mu\text{s}$	$I_C = 2 \text{ mA}, V_{CE} = 10 \text{ V}, R_L = 100 \Omega$
Turn-off time	$t_{off}$		4		$\mu\text{s}$	$I_F = 2 \text{ mA}, V_{CE} = 10 \text{ V}, R_L = 100 \Omega$
Turn-on time	$t_{on}$		6.5		$\mu\text{s}$	$I_F = 10 \text{ mA}, V_{CE} = 5 \text{ V}, R_L = 10K\Omega$
Turn-off time	$t_{off}$		165		$\mu\text{s}$	$I_F = 10 \text{ mA}, V_{CE} = 5 \text{ V}, R_L = 10K\Omega$

#### ISOLATION CHARACTERISTICS

CHARACTERISTICS	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
Surge isolation voltage	$V_{ISO}$	6000			$V_{Peak}$	1 Minute
Steady-state isolation voltage	$V_{ISO}$	5300			$V_{RMS}$	1 Minute
Isolation resistance	$R_{ISO}$	$10^{11}$			ohms	$V_{IO} = 500 \text{ VDC}$
Isolation capacitance	$C_{ISO}$		0.5		pF	$V_{IO} = 0, f = 1 \text{ MHz}$



## PHOTOTRANSISTOR OPTOCOUPLEDERS

### TYPICAL ELECTRICAL CHARACTERISTIC CURVES

(25°C Free Air Temperature Unless Otherwise Specified)




Fig. 1. Output Current vs. Input Current




Fig. 2. Output Current vs. Temperature




Fig. 3. Input Characteristics




Fig. 4. Output Characteristics




Fig. 5. Switching Speed vs.  $R_L$




Fig. 6. Leakage Current vs. Temperature



## PHOTOTRANSISTOR OPTOCOUPLEDERS

---

### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.