

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Fairchild Semiconductor](#)
[MST6111C](#)

For any questions, you can email us directly:


sales@integrated-circuit.com

FAIRCHILD
SEMICONDUCTOR™

**0.56 INCH (14.2 MM)
THREE DIGIT STICK DISPLAY**

**BRIGHT RED MST6111C, MST6141C
GREEN MST6411C, MST6441C
HIGH EFF. RED MST6911C, MST6941C**

PACKAGE DIMENSIONS



NOTES: Dimensions are in mm (inch).
All pins are 0.5 (0.02) diameter
Tolerances are ± 0.25 (0.1) unless otherwise noted.

FEATURES

Easy to read digit
Common anode or cathode
Low power consumption
Highly visible bold segments
High brightness with high contrast
White segments on a grey face for
MST64X1C and MST61X1C.
Red segments and red face for
MST69X1C
Directly compatible with integrated
circuits
Rugged plastic/epoxy construction

APPLICATIONS

Digital readout displays
Instrument panels

MODEL NUMBERS

<u>Part number</u>	<u>Color</u>	<u>Description</u>
MST6111C	Bright Red	Common Anode; right hand decimal
MST6141C	Bright Red	Common Cathode; right hand decimal
MST6411C	Green	Common Anode; right hand decimal
MST6441C	Green	Common Cathode; right hand decimal
MST6911C	High Efficiency Red	Common Anode; right hand decimal
MST6941C	High Efficiency Red	Common Cathode; right hand decimal

(For other color options, contact your local area Sales Office)

FAIRCHILD
SEMICONDUCTOR™

**0.56 INCH (14.2 MM)
THREE DIGIT STICK DISPLAY**

ABSOLUTE MAXIMUM RATING (T_A=25°C unless otherwise specified)

Part number	B.Red MST 6111C 6141C	Green MST 6411C 6441C	High Eff. Red MST 6911C 6941C	Unit
Continuous forward current (I _F)				
Per Segment	15	30	30	mA
Peak forward current per die (I _F) (at f = 10.0 KHz, Duty factor = 1/10)	60	90	90	mA
Power dissipation (P _D)	40*	70*	70*	mW
*Derate Linearly from 25°C	0.17	0.33	0.33	mW/°C
Reverse voltage per dice.....	5V			
Operating and Storage temperature range.....	- 25°C to +85°C			
Lead soldering time (at 1/16 inch from the bottom of lamp).....	5 seconds @ 230°C			

ELECTRO - OPTICAL CHARACTERISTICS (T_A = 25°C unless otherwise specified)


Part number	Bright Red MST 6111C 6141C	Green MST 6411C 6441C	High Eff. Red MST 6911C 6941C	Test Condition
Luminous intensity (ucd)				
minimum	300	800	900	I _F = 20mA
typical	700	2200	2200	I _F = 20mA
Forward voltage (V _F)				
typical	2.1	2.1	2.0	I _F = 20mA
maximum	2.6	2.8	2.8	
Peak wavelength (nm)	697	570	635	I _F = 20mA
Spectral line half width (nm)	90	30	45	I _F = 20mA
Reverse breakdown voltage (V _R)	5	5	5	I _R = 100uA

FAIRCHILD
SEMICONDUCTOR™


**0.56 INCH (14.2 MM)
THREE DIGIT STICK DISPLAY**

PINOUT

MST6X11C - Common Anode



MST6X41C - Common Cathode



FAIRCHILD

SEMICONDUCTOR™

0.56 INCH (14.2 MM) THREE DIGIT STICK DISPLAY

GRAPHICAL DATA - Bright Red ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT VS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig.6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE $f = 1 \text{ KHz}$)

FAIRCHILD
SEMICONDUCTOR™

**0.56 INCH (14.2 MM)
THREE DIGIT STICK DISPLAY**

GRAPHICAL DATA - Green ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE





Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT CS. A FUNCTION OF AMBIENT TEMPERATURE.



**Fig. 6 MAX PEAK CURRENT VS. DUTY CYCLE %
(REFRESH RATE $f = 1 \text{ KHz}$)**

FAIRCHILD

SEMICONDUCTOR™

0.56 INCH (14.2 MM) THREE DIGIT STICK DISPLAY

GRAPHICAL DATA - High Efficiency Red ($T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




Fig.2 SPECTRAL RESPONSE




Fig.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.5 LUMINOUS INTENSITY VS. DUTY CYCLE




Fig.4 MAXIMUM ALLOWABLE DC CURRENT PER SEGMENT VS. A FUNCTION OF AMBIENT TEMPERATURE.




Fig. 6 MAX PEAK CURRENT VS. DUTY CYCLE % (REFRESH RATE $f = 1 \text{ KHz}$)



0.56 INCH (14.2 MM) THREE DIGIT STICK DISPLAY

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.