

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Vishay/Dale](#)
[IFCB0603ER18NG](#)

For any questions, you can email us directly:


sales@integrated-circuit.com



IFCB-0603

Vishay Dale

Thin Film Chip Inductors



STANDARD ELECTRICAL SPECIFICATIONS

L 500 MHz (nH)	L TOL.	Q TYPICAL			SRF TYP. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)
		100 MHz	800 MHz	1700 MHz			
1.0	0.3 nH	13	34	49	13 000	0.35	800
1.2	0.3 nH	13	34	49	13 000	0.35	800
1.5	0.3 nH	13	34	49	10 000	0.35	800
1.8	0.3 nH	13	34	49	10 000	0.35	300
2.2	0.3 nH	13	34	49	8000	0.35	300
2.7	0.3 nH	13	34	49	6000	0.45	300
3.3	0.3 nH	13	34	49	6000	0.45	300
3.9	0.3 nH	13	34	49	6000	0.45	300
4.7	0.3 nH	13	34	41	5000	0.55	300
5.6	0.3 nH	13	34	41	5000	0.65	300
6.8	0.3 nH	13	34	41	5000	0.75	300
8.2	0.3 nH	13	34	41	4000	0.95	300
10	2 %, 5 %	13	34	30	4000	0.95	300
12	2 %, 5 %	13	30	30	3000	1.05	300
15	2 %, 5 %	13	30	30	3000	1.35	300
18	2 %, 5 %	13	30	25	2000	1.65	300
22	2 %, 5 %	13	30	25	2000	1.95	250
27	2 %, 5 %	10	45	25	2000	2.35	250
33	2 %, 5 %	10	45	6	1500	2.75	250
39	2 %, 5 %	10	45	1	1500	3.00	200
47	2 %, 5 %	10	45	1	1500	3.00	200
56	2 %, 5 %	10	26	4	1000	5.00	150
68	2 %, 5 %	10	26	6	1000	5.00	150

FEATURES

- Tight tolerance
- Self-resonant frequency controlled within 10 %
- Stable inductance over high frequencies
- Compatible with reflow or flow soldering
- Temperature range: - 40 °C to + 125 °C (no load)
- 40 °C to + 85 °C (full rated current)
- Compliant to RoHS directive 2002/95/EC




APPLICATIONS

- Cellular telephone, pagers and GPS products
- Wireless LAN and other communication appliances
- VCO, TCXO circuit and RF transceiver module

DIMENSIONS in inches [millimeters]

MODEL	A	B	C	D
IFCB-0603	0.063±0.004 [1.60 ± 0.10]	0.031±0.004 [0.80 ± 0.10]	0.018±0.004 [0.45 ± 0.10]	0.012±0.008 [0.30 ± 0.20]

PERFORMANCE GRAPHS: INDUCTANCE AND Q VS. FREQUENCY



DESCRIPTION

IFCB-0603	10 nH	± 5 %	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER

I	F	C	B	0	6	0	3	E	R	1	0	N	J
PRODUCT FAMILY				SIZE				PACKAGE CODE		INDUCTANCE VALUE			TOL.



www.vishay.com

Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.