

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Vishay Semiconductor/Opto Division](#)
[VLPC0401A2J](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

High Brightness LED Power Module



22139

DESCRIPTION

VLPC0401A2J is a metal core based high brightness LED power modules assembled with 4 white LED's. Color temperature range of 5000 K to 7000 K.

PRODUCT GROUP AND PACKAGE DATA

- Product group: LED
- Package: LED module
- Product series: power
- Angle of half intensity: $\pm 80^\circ$

FEATURES

- Metal core PCB: Al > 1 mm thickness
- Single side/single layer PCB
- Shiny white surface
- 4 LED's in a row
- Conductive top layer: Cu (min. 18 μm)
- Isolation layer prepreg (100 μm)
- ESD withstand voltage: up to 2 kV according to JESD22-A114-B
- Color binning
- LM80 certified LEDs
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS

COMPLIANT

GREEN
(IEC-2008)

APPLICATIONS

- Internal lighting in buildings
- Tunnel lights
- Reading lamp, table lamp
- General lighting application

PARTS TABLE

PART	COLOR	LUMINOUS FLUX (at $I_F = 700$ mA typ.)	COLOR TEMPERATURE K	TECHNOLOGY
VLPC0401A2J	Cool white	$\Phi_V = \text{typ. } 580 \text{ lm}$	5000 to 7000	InGaN

ABSOLUTE MAXIMUM RATINGS ($T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified) **VLPC0401A2J**

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Forward current		I_F	700	mA
Power dissipation	Total	P_{tot}	10.8	W
Junction temperature		T_j	120	°C
Operating temperature range		T_{amb}	- 40 to + 85	°C
Storage temperature range		T_{stg}	- 40 to + 85	°C
Decomposition temperature of PCB (for cable assembly)	3 x 10 s	T_D	350	°C

OPTICAL AND ELECTRICAL CHARACTERISTICS ($T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified) **VLPC0401A2J, COOL WHITE**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux total ⁽¹⁾	$I_F = 700$ mA	Φ_V	500	580	-	lm
Color temperature	$I_F = 700$ mA	TK	5000	-	7000	K
Forward voltage	$I_F = 700$ mA	V_F	12.5	14	15.5	V
Temperature coefficient of V_F	$I_F = 350$ mA	TC_{VF}	-	- 14	-	mV/K
Temperature coefficient of Φ_V	$I_F = 350$ mA	$TC\Phi_V$	-	- 0.4	-	%/K


Notes

- Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of ± 0.1 V. Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of $\pm 11\%$.

⁽¹⁾ Calculated based on single LED unit.


COLOR RANGE AND COLOR BINNING

VLPC0401A2J: 5000 K to 7000 K group 6P to 7R



CHROMATICITY COORDINATED GROUPS FOR COOL WHITE SMD LED											
GROUP	X	Y	GROUP	X	Y	GROUP	X	Y	GROUP	X	Y
6P	0.309	0.302	6Q	0.307	0.311	6R	0.305	0.322			
	0.307	0.311		0.305	0.322		0.304	0.329			
	0.317	0.331		0.317	0.346		0.317	0.356			
	0.317	0.318		0.317	0.331		0.317	0.346			
7P	0.317	0.318	7Q	0.317	0.331	7R	0.317	0.356			
	0.317	0.331		0.317	0.356		0.322	0.365			
	0.334	0.365		0.334	0.365		0.330	0.373			
	0.338	0.360		0.317	0.331		0.334	0.365			

PCB BASIC DESIGN DIMENSIONS in millimeters




Drawing-No.: 9.920-6790.01-4

Issue: 1; 05.09.11

Not indicated tolerances ± 0.2

Drawing refers to following types: VLPC0401A2J



technical drawings
according to DIN
specifications

PCB CHARACTERISTICS

- Metal core PCB: Al (minimum 1000 μm - thickness)
- Prepreg minimum 63 μm
- Conductive pattern Cu minimum 18 μm
- Free of burrs
- RoHS compliant
- Halogen-free
- Solder resist on top side
- Shiny white surface (glossy-white Taiyo-PSR 2000)
- Galvanic of solder pads and backside pure matte Sn (0.8 μm to 1.2 μm)
- Assembled with 4 high brightness power LEDs. LED position accuracy ± 0.3

EMISSION CHARACTERISTIC





Fig. 2 - Relative Luminous Intensity vs. Angular Displacement

BAR CODE PRODUCT LABEL



A. Type of component

B. Manufacturing plant

C. SEL - selection code (bin):

X = color group

D. Batch:

200707 = year 2007, week 07

PH19 = plant code

E. Total quantity

Note

- 32 PCB's per box, minimum order quantity 32



Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.