Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

Mueller Electric Co.
BU-P2249-C-48

For any questions, you can email us directly:
sales@integrated-circuit.com

MODEL: BU-P2249-C-XX

Test Lead, BNC (M) on Each End, RG-58C/U

- Materials:
  - Cable: Cable is RG 58C/U, complies to Mil-M17/155-00001
    Jacket is non-contaminating PVC
    Center conductor is 20 AWG (19x33) tinned copper
    Shield is tinned copper braid (95% coverage)
  - Male BNC: Body is tarnish resistant nickel plated brass
    Center Contact is Gold plated brass
    Insulator is PTFE
  - Strain Relief is Molded PVC that is bonded to the BNC.

- Ratings: Impedance: 50 Ohms
  Capacitance per foot: 30.8 pf
  Power Loss/100 Ft. @ 1 MHz: .40 dB
  Hands free testing to 1400 VRMS
  Operating Temperature: -40°C to 85°C

- Ordering: The "XX" in the part number represents the length in Inches. Standard lengths are:
  6", 12", 24", 36", 48", 60", 72", 120", 144" 180", 240", 300", and 600"

- RoHS Compliant, CE Compliant