

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Texas Instruments](#)
[CSD18532NQ5B](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CSD18532NQ5B 60 V N-Channel NexFET™ Power MOSFET

1 Features

- Ultra-Low Q_g and Q_{gd}
- Low Thermal Resistance
- Avalanche Rated
- Pb Free Terminal Plating
- RoHS Compliant
- Halogen Free
- SON 5 mm x 6 mm Plastic Package

Product Summary

| $T_A = 25^\circ\text{C}$ | | TYPICAL VALUE | | UNIT |
|--------------------------|-------------------------------|------------------------|-----|------------------|
| V_{DS} | Drain-to-Source Voltage | 60 | | V |
| Q_g | Gate Charge Total (10 V) | 49 | | nC |
| Q_{gd} | Gate Charge Gate to Drain | 7.9 | | nC |
| $R_{DS(on)}$ | Drain-to-Source On-Resistance | $V_{GS} = 6\text{ V}$ | 3.5 | $\text{m}\Omega$ |
| | | $V_{GS} = 10\text{ V}$ | 2.7 | $\text{m}\Omega$ |
| $V_{GS(th)}$ | Threshold Voltage | 2.8 | | V |

2 Applications

- DC-DC Conversion
- Secondary Side Synchronous Rectifier
- Isolated Converter Primary Side Switch
- Motor Control


Ordering Information

| DEVICE | QTY | MEDIA | PACKAGE | SHIP |
|---------------|------|--------------|---------------------------------|---------------|
| CSD18532NQ5B | 2500 | 13-Inch Reel | SON 5 mm x 6 mm Plastic Package | Tape and Reel |
| CSD18532NQ5BT | 250 | 7-Inch Reel | | |

3 Description

This 60 V, 2.7 mΩ, 5 x 6 mm SON NexFET™ power MOSFET has been designed to minimize losses in power conversion applications.

Top View





P0093-01

Absolute Maximum Ratings

| $T_A = 25^\circ\text{C}$ | | VALUE | UNIT |
|--------------------------|---|------------|------|
| V_{DS} | Drain to Source Voltage | 60 | V |
| V_{GS} | Gate to Source Voltage | ± 20 | V |
| I_D | Continuous Drain Current (Package limited) | 100 | |
| | Continuous Drain Current (Silicon limited), $T_C = 25^\circ\text{C}$ | 151 | A |
| | Continuous Drain Current ⁽¹⁾ | 21 | |
| I_{DM} | Pulsed Drain Current ⁽²⁾ | 400 | A |
| P_D | Power Dissipation ⁽¹⁾ | 3.1 | |
| | Power Dissipation, $T_C = 25^\circ\text{C}$ | 156 | W |
| $T_{J, T_{stg}}$ | Operating Junction Temperature, Storage Temperature | -55 to 150 | °C |
| E_{AS} | Avalanche Energy, single pulse $I_D = 85\text{ A}$, $L = 0.1\text{ mH}$, $R_G = 25\text{ }\Omega$ | 360 | mJ |

(1) Typical $R_{DS(on)} = 40^\circ\text{C}/\text{W}$ on a 1 inch², 2 oz. Cu pad on a 0.06 inch thick FR4 PCB.

(2) Max $R_{DS(on)} = 0.8^\circ\text{C}/\text{W}$, Pulse duration $\leq 100\text{ }\mu\text{s}$, duty cycle $\leq 1\%$.



An **IMPORTANT NOTICE** at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. **PRODUCTION DATA**.

CSD18532NQ5B

SLPS440A – JUNE 2013 – REVISED DECEMBER 2015

www.ti.com**Table of Contents**

| | | | | | |
|----------|---|----------|----------|---|----|
| 1 | Features | 1 | 6.1 | Community Resources | 7 |
| 2 | Applications | 1 | 6.2 | Trademarks | 7 |
| 3 | Description | 1 | 6.3 | Electrostatic Discharge Caution | 7 |
| 4 | Revision History | 2 | 6.4 | Glossary | 7 |
| 5 | Specifications | 3 | 7 | Mechanical, Packaging, and Orderable | |
| 5.1 | Electrical Characteristics | 3 | | Information | 8 |
| 5.2 | Thermal Information | 3 | 7.1 | Q5B Package Dimensions | 8 |
| 5.3 | Typical MOSFET Characteristics | 4 | 7.2 | Recommended PCB Pattern | 9 |
| 6 | Device and Documentation Support | 7 | 7.3 | Recommended Stencil Pattern | 9 |
| | | | 7.4 | Q5B Tape and Reel Information | 10 |

4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Original (June 2014) to Revision A | Page |
|---|-------------|
| • Added part number to title | 1 |
| • Added 7" reel to <i>Ordering Information</i> | 1 |
| • Updated pulsed current conditions | 1 |
| • Added line for Power Dissipation, $T_C = 25^\circ\text{C}$ in <i>Absolute Maximum Ratings</i> table | 1 |
| • Updated Figure 1 to show R_{thJC} curves | 4 |
| • Updated SOA in Figure 10 | 6 |
| • Added <i>Device and Documentation Support</i> section | 7 |
| • Updated <i>Mechanical, Packaging, and Orderable Information</i> and mechanical drawings | 8 |

5 Specifications

5.1 Electrical Characteristics

($T_A = 25^\circ\text{C}$ unless otherwise stated)

| PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|-----------------------------------|---------------------------------------|--|------|------|---------------|
| STATIC CHARACTERISTICS | | | | | |
| BV_{DSS} | Drain-to-source voltage | $\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{I}_D = 250 \mu\text{A}$ | 60 | | V |
| I_{DSS} | Drain-to-source leakage current | $\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{V}_{\text{DS}} = 48 \text{ V}$ | | 1 | μA |
| I_{GSS} | Gate-to-source leakage current | $\text{V}_{\text{DS}} = 0 \text{ V}$, $\text{V}_{\text{GS}} = 20 \text{ V}$ | | 100 | nA |
| $\text{V}_{\text{GS}(\text{th})}$ | Gate-to-source threshold voltage | $\text{V}_{\text{DS}} = \text{V}_{\text{GS}}$, $\text{I}_D = 250 \mu\text{A}$ | 2.4 | 2.8 | 3.4 |
| $\text{R}_{\text{DS}(\text{on})}$ | Drain-to-source on-resistance | $\text{V}_{\text{GS}} = 6 \text{ V}$, $\text{I}_D = 25 \text{ A}$ | | 3.5 | 4.4 |
| | | $\text{V}_{\text{GS}} = 10 \text{ V}$, $\text{I}_D = 25 \text{ A}$ | | 2.7 | 3.4 |
| g_{fs} | Transconductance | $\text{V}_{\text{DS}} = 30 \text{ V}$, $\text{I}_D = 25 \text{ A}$ | 140 | | S |
| DYNAMIC CHARACTERISTICS | | | | | |
| C_{iss} | Input capacitance | $\text{V}_{\text{GS}} = 0 \text{ V}$, $\text{V}_{\text{DS}} = 30 \text{ V}$, $f = 1 \text{ MHz}$ | 4100 | 5340 | pF |
| C_{oss} | Output capacitance | | 495 | 644 | pF |
| C_{rss} | Reverse transfer capacitance | | 16 | 21 | pF |
| R_G | Series gate resistance | | 1.2 | 2.4 | Ω |
| Q_g | Gate charge total (10 V) | $\text{V}_{\text{DS}} = 30 \text{ V}$, $\text{I}_D = 25 \text{ A}$ | 49 | 64 | nC |
| Q_{gd} | Gate charge gate to drain | | 7.9 | | nC |
| Q_{gs} | Gate charge gate to source | | 16 | | nC |
| $\text{Q}_{\text{g}(\text{th})}$ | Gate charge at V_{th} | | 11 | | nC |
| Q_{oss} | Output charge | $\text{V}_{\text{DS}} = 30 \text{ V}$, $\text{V}_{\text{GS}} = 0 \text{ V}$ | 69 | | nC |
| $\text{t}_{\text{d}(\text{on})}$ | Turn on delay time | $\text{V}_{\text{DS}} = 30 \text{ V}$, $\text{V}_{\text{GS}} = 10 \text{ V}$, $\text{I}_{\text{DS}} = 25 \text{ A}$, $\text{R}_G = 0 \Omega$ | 8.2 | | ns |
| t_r | Rise time | | 8.7 | | ns |
| $\text{t}_{\text{d}(\text{off})}$ | Turn off delay time | | 20 | | ns |
| t_f | Fall time | | 2.7 | | ns |
| DIODE CHARACTERISTICS | | | | | |
| V_{SD} | Diode forward voltage | $\text{I}_{\text{SD}} = 25 \text{ A}$, $\text{V}_{\text{GS}} = 0 \text{ V}$ | 0.8 | 1 | V |
| Q_{rr} | Reverse recovery charge | $\text{V}_{\text{DS}} = 30 \text{ V}$, $\text{I}_F = 25 \text{ A}$, $d\text{I}/dt = 300 \text{ A}/\mu\text{s}$ | 139 | | nC |
| t_{rr} | Reverse recovery time | | 64 | | ns |

5.2 Thermal Information

($T_A = 25^\circ\text{C}$ unless otherwise stated)

| THERMAL METRIC | | MIN | TYP | MAX | UNIT |
|-------------------------|--|-----|-----|-----|---------------------------|
| $\text{R}_{\text{θJC}}$ | Junction-to-case thermal resistance ⁽¹⁾ | | | 0.8 | $^\circ\text{C}/\text{W}$ |
| $\text{R}_{\text{θJA}}$ | Junction-to-ambient thermal resistance ⁽¹⁾⁽²⁾ | | | 50 | $^\circ\text{C}/\text{W}$ |



(1) $\text{R}_{\text{θJC}}$ is determined with the device mounted on a 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu pad on a 1.5 inch \times 1.5 inch (3.81 cm \times 3.81 cm), 0.06 inch (1.52 mm) thick FR4 PCB. $\text{R}_{\text{θJC}}$ is specified by design, whereas $\text{R}_{\text{θJA}}$ is determined by the user's board design.

(2) Device mounted on FR4 material with 1 inch² (6.45 cm²), 2 oz. (0.071 mm thick) Cu.

CSD18532NQ5B

SLPS440A – JUNE 2013 – REVISED DECEMBER 2015

www.ti.com



5.3 Typical MOSFET Characteristics

($T_A = 25^{\circ}\text{C}$ unless otherwise stated)




Figure 1. Transient Thermal Impedance

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 2. Saturation Characteristics




Figure 3. Transfer Characteristics




Figure 4. Gate Charge




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature




Figure 7. On-State Resistance vs Gate-to-Source Voltage

CSD18532NQ5B

SLPS440A – JUNE 2013 – REVISED DECEMBER 2015

www.ti.com

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 8. Normalized On-State Resistance vs Temperature




Figure 9. Typical Diode Forward Voltage




Figure 10. Maximum Safe Operating Area




Figure 11. Single Pulse Unclamped Inductive Switching




Figure 12. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

TI E2E™ Online Community *TI's Engineer-to-Engineer (E2E) Community.* Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

Design Support *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

6.2 Trademarks

NexFET, E2E are trademarks of Texas Instruments.

All other trademarks are the property of their respective owners.

6.3 Electrostatic Discharge Caution

 These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

6.4 Glossary

[SLYZ022 — TI Glossary](#).

This glossary lists and explains terms, acronyms, and definitions.

CSD18532NQ5B


SLPS440A –JUNE 2013–REVISED DECEMBER 2015

www.ti.com

7 Mechanical, Packaging, and Orderable Information


The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 Q5B Package Dimensions




| DIM | MILLIMETERS | | |
|-----|-------------|------|------|
| | MIN | NOM | MAX |
| A | 0.80 | 1.00 | 1.05 |
| b | 0.36 | 0.41 | 0.46 |
| c | 0.15 | 0.20 | 0.25 |
| c1 | 0.15 | 0.20 | 0.25 |
| c2 | 0.20 | 0.25 | 0.30 |
| D1 | 4.90 | 5.00 | 5.10 |
| D2 | 4.12 | 4.22 | 4.32 |
| d | 0.20 | 0.25 | 0.30 |
| E | 4.90 | 5.00 | 5.10 |
| E1 | 5.90 | 6.00 | 6.10 |
| E2 | 3.48 | 3.58 | 3.68 |
| e | 1.27 TYP | | |
| L | 0.46 | 0.56 | 0.66 |
| θ | 0° | — | — |
| K | 1.40 TYP | | |

7.2 Recommended PCB Pattern



For recommended circuit layout for PCB designs, see application note [SLPA005 – Reducing Ringing Through PCB Layout Techniques](#).

7.3 Recommended Stencil Pattern




CSD18532NQ5B

SLPS440A – JUNE 2013 – REVISED DECEMBER 2015

www.ti.com

7.4 Q5B Tape and Reel Information



Notes:

1. 10-sprocket hole-pitch cumulative tolerance ±0.2
2. Camber not to exceed 1 mm in 100 mm, noncumulative over 250 mm
3. Material: black static-dissipative polystyrene
4. All dimensions are in mm (unless otherwise specified)
5. A0 and B0 measured on a plane 0.3 mm above the bottom of the pocket

PACKAGING INFORMATION

| Orderable Device | Status (1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan (2) | Lead/Ball Finish (6) | MSL Peak Temp (3) | Op Temp (°C) | Device Marking (4/5) | Samples |
|------------------|---------------|--------------|--------------------|------|----------------|--------------------------|-------------------------|----------------------|--------------|-------------------------|---|
| CSD18532NQ5B | ACTIVE | VSON-CLIP | DNK | 8 | 2500 | Pb-Free (RoHS Exempt) | CU SN | Level-1-260C-UNLIM | -55 to 150 | 18532N | Samples |
| CSD18532NQ5BT | ACTIVE | VSON-CLIP | DNK | 8 | 250 | Pb-Free (RoHS Exempt) | CU SN | Level-1-260C-UNLIM | -55 to 150 | 18532N | Samples |

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.


(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



| | |
|----|---|
| A0 | Dimension designed to accommodate the component width |
| B0 | Dimension designed to accommodate the component length |
| K0 | Dimension designed to accommodate the component thickness |
| W | Overall width of the carrier tape |
| P1 | Pitch between successive cavity centers |


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| CSD18532NQ5B | VSON-CLIP | DNK | 8 | 2500 | 330.0 | 12.8 | 6.5 | 5.3 | 1.4 | 8.0 | 12.0 | Q1 |
| CSD18532NQ5BT | VSON-CLIP | DNK | 8 | 250 | 330.0 | 12.8 | 6.5 | 5.3 | 1.4 | 8.0 | 12.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| CSD18532NQ5B | VSON-CLIP | DNK | 8 | 2500 | 335.0 | 335.0 | 32.0 |
| CSD18532NQ5BT | VSON-CLIP | DNK | 8 | 250 | 335.0 | 335.0 | 32.0 |

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

| Products | Applications |
|------------------------------|--|
| Audio | www.ti.com/audio |
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DLP® Products | www.dlp.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| OMAP Applications Processors | www.ti.com/omap |
| Wireless Connectivity | www.ti.com/wirelessconnectivity |
| | TI E2E Community |
| | e2e.ti.com |