

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[117-00019](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

117-00019



Article Number: 117-00019

Double Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 1,000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 117-00019

Type T50SDH

Color Black (BK)

Features and Benefits

- Design allows the fastening of two separate bundles.
- The tie's second loop may can serve as a positioning device for a single bundle.

Product Description The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Double Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 6.3 "

Length L (Metric) 159.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter 1st Loop Max. (Imperial) 1.4 "

Bundle Diameter 1st Loop Max. (Metric) 35.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66**Flammability** UL94 V2**Halogenfree** Yes**Operating Temperature** -40°F to +185°F (-40°C to +85°C)**ROHS Compliant** Yes**UL Listed (US and Canada)** No**UL Recognized (US and Canada)** Yes