

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[PC15FT7](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

PC15FT7



Article Number: 151-14303

Fir Tree Mount Tube Clip Mounting Hole Dia .25" Panel Thickness .12" PA66HIRHS, Black 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number PC15FT7

Type PC15FT7

Color Black (BK)

Features and Benefits The clips CTC and PC are designed for fixation and bundling of convoluted tubes and pipes. Due to several designs and fixing parts, the clips can be use for nearly every application.

Short Description Fir Tree Mount Tube Clip Mounting Hole Dia .25" Panel Thickness .12" PA66HIRHS, Black 100/pkg

Product Dimensions

Length L (Imperial) 0.62 "

Length L (Metric) 15.7 mm

Fixation Method Fir Tree

Width W (Imperial) 0.85 "

Width W (Metric) 21.6 mm

Height H (Imperial) 1.5 "

Height H (Metric) 38.1 mm

Height H2 (Imperial) 1.07 "

Height H2 (Metric) 26.7 mm

Bundle Diameter Max. (Imperial) 0.62 "

Bundle Diameter Max. (Metric) 15.7 mm

Disc Diameter (Imperial) 0.9 "

Disc Diameter (Metric) 21.6 mm

Panel Thickness Max. (Imperial) 0.31 "

Panel Thickness Max. (Metric) 6.0 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 1.0 mm

Mounting Hole Diameter D (Metric) 6.4 - 6.8 mm

Mounting Hole Diameter D Min. (Imperial) 0.26 "

Mounting Hole Diameter D Max. 0.26 "

(Imperial)

Mounting Hole Diameter D Max. 6.8 mm

(Metric)

6.4 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging



Package Quantity (Metric) 1000

Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes