

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[MB3A10M4](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## MB3A10M4



**Article Number: 151-28721**

**Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 1000/pkg**



Download spec sheet

### Base Data

**Local Order Number** MB3A10M4

**Type** MB3A

**Color** White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with acrylic based adhesive backing for heavy bonding applications
  - Can also be secured using two or four screws; providing multiple options.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 1000/pkg

### Product Dimensions

**Length L (Imperial)** 0.75 "

**Length L (Metric)** 19.0 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 0.75 "

**Width W (Metric)** 19.0 mm

**Cable Tie Width Max. (Imperial)** 0.14 "

**Cable Tie Width Max. (Metric)** 3.6 mm

**Height H (Imperial)** 0.18 "

**Height H (Metric)** 4.6 mm

**Mounting Hole Diameter D (Imperial)** 0.12 "

**Mounting Hole Diameter D (Metric)** 3.0 mm

**Mounting Hole Centers (Imperial)** 0.52 "

**Thickness of Adhesive TA (Imperial)** 0.031 "

**Mounting Hole Diameter D Max.** 3.0 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 3.0 mm

**Thickness of Adhesive TA (Metric)** 0.8 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 1000

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive Shortcut</b>	Synthetic rubber T50
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Adhesive Operating Temperature</b>	-4°F to +122°F (-20°C to +50°C)
<b>Flammability</b>	UL94 V2 (excluding adhesive)
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes