

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T18R2HALM4](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

T18R2HALM4



Article Number: 111-01902

High Temp Cable Tie, 4" Long, 14lb Tensile Strength, PAHL, Red, 1000/pkg



Download spec sheet

Base Data

Local Order Number T18R2HALM4

Type T18R

Color Red (RD)

- Features and Benefits**
- Halar cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
 - Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description High Temp Cable Tie, 4" Long, 14lb Tensile Strength, PAHL, Red, 1000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 14.0 lbs

Minimum Tensile Strength (Metric) 62.0 N

Length L (Imperial) 4.0 "

Length L (Metric) 100.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.1 "

Width W (Metric) 2.45 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 0.86 "

Bundle Diameter Max. (Metric) 22.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 10000



Material and Specifications

Material	Polyamide 6.6 (E/CTFE)
Material Shortcut	PA66E/CTFE
Flammability	UL94 V0
Operating Temperature	-103°F to +302°F (-75°C to +150°C)
ROHS Compliant	Yes
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No