

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T50R2HALM4](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T50R2HALM4



Article Number: 111-04897

High Temp Tie, 8" Long, 40 lb Tensile Strength, PAHL, Red, 1000/pkg



Download spec sheet

### Base Data

Local Order Number T50R2HALM4

Type T50R

Color Red (RD)

- Features and Benefits**
- Halar cable ties provide excellent resistance to chemicals, radiation, high temperatures and UV exposure.
  - Inside serrations allow for strong hold on cables and wire bundles.
  - Head design provides high tensile strength with very low insertion force.
  - Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** High Temp Tie, 8" Long, 40 lb Tensile Strength, PAHL, Red, 1000/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 40.0 lbs

Minimum Tensile Strength (Metric) 180.0 N

Length L (Imperial) 8.0 "

Length L (Metric) 203.2 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.2 "

Width W (Metric) 5.0 mm

Bundle Diameter Min. (Imperial) 0.5 "

Bundle Diameter Min. (Metric) 12.7 mm

Bundle Diameter Max. (Imperial) 1.75 "

Bundle Diameter Max. (Metric) 44.5 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Carton Quantity 5000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (E/CTFE)
<b>Material Shortcut</b>	PA66E/CTFE
<b>Flammability</b>	UL94 V0
<b>Operating Temperature</b>	-103°F to +302°F (-75°C to +150°C)
<b>ROHS Compliant</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No