

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[151-00651](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

151-00651



Article Number: 151-00651

Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 18.0mm, PA66HIRHSUV, Natural, 2000/box



Download drawing



Download spec sheet

## Base Data

Local Order Number 151-00651

Type TC6FT6LG

Color Natural (NA)

**Features and Benefits**

- Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.

**Product Description** HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.

**Short Description** Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 18.0mm, PA66HIRHSUV, Natural, 2000/box

## Product Dimensions

Length L (Imperial) 1.5 "

Length L (Metric) 38.1 mm

Fixation Method Fir Tree

Width W (Imperial) 0.5 "

Width W (Metric) 12.0 mm

Height H (Imperial) 1.0 "

Height H (Metric) 26.6 mm

Height H2 (Imperial) 0.9 "

Height H2 (Metric) 23.1 mm

Panel Thickness Max. (Imperial) 0.71 "

Panel Thickness Max. (Metric) 18.0 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.7 mm

Mounting Hole Diameter D (Imperial) 0.26 "

Mounting Hole Diameter D (Metric) 6.5 mm

Mounting Hole Diameter D Min. (Imperial) 0.24 "

Mounting Hole Diameter D Max. 0.24 " (Imperial)

Mounting Hole Diameter D Max. 6.5 mm (Metric)

Mounting Hole Diameter D Min. (Metric) 6.5 mm

## Logistics and Packaging

Quantity Per box

**Carton Quantity** 2000

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

**Material Shortcut** PA66HIRHS

**Flammability** UL94 HB

**Operating Temperature** -40°F to +230°F (-40°C to +110°C)

**ROHS Compliant** Yes