

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[170-03014](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03014



**Article Number: 170-03014**

**Fray Resistant Expandable Braided Sleeveing, 1.0" Dia., PET, Black, 50.0 ft/Standard Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03014

**Type** BSPSC100

**Color** Black (BK)

**Features and Benefits**

- Cuts with scissors without fraying ends enables field installations without need for hot knife.
- Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.
- Expands to 150% of easy installation and reduced assembly time requirements.

**Product Description** A versatile and economical general purpose braided sleeveing that resists fraying when cut with ordinary scissors.

**Short Description** Fray Resistant Expandable Braided Sleeveing, 1.0" Dia., PET, Black, 50.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 50.0 ft

**Length L (Metric)** 15.2 m

**Reel Length (imperial)** 50.0 ft

**Bundle Diameter Min. (Imperial)** 0.75 "

**Bundle Diameter Min. (Metric)** 19.1 mm

**Bundle Diameter Max. (Imperial)** 1.19 "

**Bundle Diameter Max. (Metric)** 30.2 mm

**Nominal Diameter (Imperial)** 1 "

**Nominal Diameter (Metric)** 25.4 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 50 ft

**Package Quantity (Metric)** 50.0 ft

**Weight (imperial)** 0.62 lbs

**Weight (Metric)** 0.28 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL94 V0

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03014 - FRAY RESIS SLEEVING 1"DIA BLACK

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**UL Recognized (US and Canada)** Yes