

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[161-64507](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

161-64507



Article Number: 161-64507

Helawrap, HWPP30, 1-1/4" (30mm) Dia., PP, Black, 100ft/Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 161-64507

Type HWPP30

Color Black (BK)

Features and Benefits

- Unique open design for easy branch-offs at any point along the harness.
- Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
- Flexible construction and design eliminates pinch points and minimizes bending fatigue, making it ideal for applications involving movement and vibration.
- Split shape allows for future access without disassembly.

Product Description The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

Short Description Helawrap, HWPP30, 1-1/4" (30mm) Dia., PP, Black, 100ft/Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Variant Spiral Binding

Bundle Diameter Min. (Imperial) 0.91 "

Bundle Diameter Min. (Metric) 23.11 mm

Bundle Diameter Max. (Imperial) 1.26 "

Bundle Diameter Max. (Metric) 32.0 mm

Diameter D (imperial) 1.25 "

Diameter D (metric) 30.0 mm

Nominal Diameter (Imperial) 1-1/4 "

Nominal Diameter (Metric) 30.0 mm

Wall Thickness WT (Imperial) 0.04 "

Wall Thickness WT (Metric) 10.41 mm

Pitch (imperial) 0.79 "

Pitch (metric) 20.07 mm

Logistics and Packaging

Quantity Per reel

Package Quantity (Metric) 30.48 m

Carton Quantity 30.48 m

Weight (Metric) 4.39 kg

Weight (imperial) 9.58 lbs

Material and Specifications

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL94 HB

Halogenfree Yes

Operating Temperature -76°F to +230°F (-60°C to +110°C)

ROHS Compliant Yes