

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[161-63403](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

161-63403



**Article Number: 161-63403**

**Helawrap, HWPAV025, 1" (25mm) Dia., PA6V0, Black, 100ft/Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 161-63403

**Type** HWPAV025

**Color** Black (BK)

**Features and Benefits**

- Unique open design allows for easy branch-offs at any point along the harness.
- Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
- Flexible construction and design is well suited for applications that involve movement and vibration.
- Easy to use installation tool makes assembly fast and easy.

**Product Description** The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

**Short Description** Helawrap, HWPAV025, 1" (25mm) Dia., PA6V0, Black, 100ft/Reel

## Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Variant** Spiral Binding

**Bundle Diameter Min. (Imperial)** 0.91 "

**Bundle Diameter Min. (Metric)** 23.11 mm

**Bundle Diameter Max. (Imperial)** 1.06 "

**Bundle Diameter Max. (Metric)** 26.92 mm

**Diameter D (imperial)** 1.0 "

**Diameter D (metric)** 25.0 mm

**Nominal Diameter (Imperial)** 1 "

**Nominal Diameter (Metric)** 25.0 mm

**Wall Thickness WT (Imperial)** 0.04 "

**Wall Thickness WT (Metric)** 1.05 mm

**Pitch (imperial)** 0.79 "

**Pitch (metric)** 20.07 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100.0 ft

**Carton Quantity** 30.48 m

**Weight (imperial)** 8.06 lbs

**Weight (Metric)** 3.66 kg

---

## Material and Specifications

**Material** Polyamide 6 V0 (PA6V0)

**Material Shortcut** PA6V0

**Flammability** UL94 V0

**Halogenfree** Yes

**Operating Temperature** -40°F to +194°F (-40°C to +90°C)

**ROHS Compliant** Yes

**Certification/Specification** UL-Recognized  
CEN TS 45545-2: 2009

**UL Recognized (US)** Yes