

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03065](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03065



Article Number: 170-03065

Aluminum Laminated Fiberglass Sleeve, 1.75" Dia., Silver, 50.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03065

Type BSHTTST134SR

Color Silver (SR)

Features and Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeve, 1.75" Dia., Silver, 50.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Max. (Imperial) 1.687 "

Bundle Diameter Max. (Metric) 42.8 mm

Nominal Diameter (Imperial) 1-3/4 "

Nominal Diameter (Metric) 44.5 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 1

Weight (imperial) 3.70 lbs

Weight (Metric) 1.68 kg

Material and Specifications

Material Glass Fiber (GF)
Aluminium (AL)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03065 - ALU FBRGLSS SLVNG 1.75"DIA SLVR

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com
