

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[RT250R9X2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## RT250R9X2



**Article Number:** 131-75019

**Releasable Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** RT250R9X2

**Type** RT250R

**Color** Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
  - Head design provides high tensile strength with very low insertion force even after repeated use.
  - Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Releasable Cable Tie, 20.3" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 250.0 lbs

**Minimum Tensile Strength (Metric)** 1115.0 N

**Length L (Imperial)** 20.3 "

**Length L (Metric)** 515.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.49 "

**Width W (Metric)** 12.5 mm

**Bundle Diameter Min. (Imperial)** 0.47 "

**Bundle Diameter Min. (Metric)** 12.0 mm

**Bundle Diameter Max. (Imperial)** 4.9 "

**Bundle Diameter Max. (Metric)** 125.0 mm

**Thickness T (Imperial)** 0.075 "

**Cable Tie Head Length (Imperial)** 0.88 "

**Cable Tie Head Width (Imperial)** 0.79 "

**Thickness T (Metric)** 1.9 mm

### Logistics and Packaging

|                                  |            |
|----------------------------------|------------|
| <b>Quantity Per</b>              | bag        |
| <b>Package Quantity (Metric)</b> | 25 Pieces  |
| <b>Carton Quantity</b>           | 500 Pieces |
| <b>Weight (Metric)</b>           | 12.2 kg    |

## Material and Specifications

---

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Material</b>                      | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>             | PA66                             |
| <b>Flammability</b>                  | UL94 V2                          |
| <b>Operating Temperature</b>         | -40°F to +185°F (-40°C to +85°C) |
| <b>ROHS Compliant</b>                | Yes                              |
| <b>Certification/Specification</b>   | UL                               |
| <b>UL Listed (US and Canada)</b>     | No                               |
| <b>UL Recognized (US and Canada)</b> | Yes                              |