

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T255M0HIRX2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T255M0HIRX2



Article Number: 111-25300

Heavy Duty Cable Tie, 22" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg



Download spec sheet

Base Data

Local Order Number T255M0HIRX2

Type T255M

Color Black (BK)

Features and Benefits

- High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 22" Long, 250 lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1115.0 N

Length L (Imperial) 22.0 "

Length L (Metric) 560.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.6 mm

Bundle Diameter Min. (Imperial) 0.49 "

Bundle Diameter Min. (Metric) 12.5 mm

Bundle Diameter Max. (Imperial) 6.3 "

Bundle Diameter Max. (Metric) 160.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 25

Carton Quantity 500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No