

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[SNP4GHS0C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## SNP4GHS0C2



Article Number: 192-10040

Snapper Hose Clamps, .41"/.458" Min/Max Diameter, PA66GF13%, Black, 100/pkg



Download spec sheet

### Base Data

Local Order Number SNP4GHS0C2

Type SNP4

Color Black (BK)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Short Description** Snapper Hose Clamps, .41"/.458" Min/Max Diameter, PA66GF13%, Black, 100/pkg

### Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.234 "

Width W2 (Metric) 5.94 mm

Bundle Diameter Min. (Imperial) 0.39 "

Bundle Diameter Min. (Metric) 10.4 mm

Bundle Diameter Max. (Imperial) 0.46 "

Bundle Diameter Max. (Metric) 11.7 mm

Diameter Min. (Imperial) 0.41 "

Diameter Min. (Metric) 10.41 mm

Diameter Max. (Imperial) 0.458 "

Diameter Max. (Metric) 11.63 mm

Nominal Diameter (Imperial) 7/16 "

Nominal Diameter (Metric) 11 mm

Wall Thickness WT (Imperial) 0.067 "

Wall Thickness WT (Metric) 1.7 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 100 Pieces

Weight (Metric) 0.18 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
<b>Material Shortcut</b>	PA66GF13
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes