

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[CTM30C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## CTM30C2



Article Number: 151-30600

Cable Tie Mount, 0.2" Hole Dia., 0.31" Max Tie Width, PA66, Black, 100/pkg



Download spec sheet

### Base Data

Local Order Number CTM30C2

Type CTM3

Color Black (BK)

**Features and Benefits**

- Designed for use with 18 through 120 pound cable ties to provide stability when securing bundles.
- Secures with a single screw providing quick installation.

**Product Description** HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.

**Short Description** Cable Tie Mount, 0.2" Hole Dia., 0.31" Max Tie Width, PA66, Black, 100/pkg

### Product Dimensions

Length L (Imperial) 0.86 "

Length L (Metric) 21.8 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 0.61 "

Width W (Metric) 15.5 mm

Cable Tie Width Max. (Imperial) 0.31 "

Cable Tie Width Max. (Metric) 7.9 mm

Height H (Imperial) 0.37 "

Height H (Metric) 9.4 mm

Mounting Hole Diameter D (Imperial) 0.2 "

Mounting Hole Diameter D (Metric) 5.1 mm

Mounting Hole Diameter D Max. 5.1 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.1 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 5000

Weight (Metric) 1 kg

### Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66



**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes