

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[MBT14S](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

MBT14S



Article Number: 111-93149

Stainless Steel Tie, 14.3" Long, 202lb Tensile Strength, SS316, Metal, 100/pkg



Download spec sheet

Base Data

Local Order Number MBT14S

Type MBT14S

Color Metal (ML)

Features and Benefits

- 316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.
- Ball bearing locking mechanism assures high tensile strength and easy insertion.

Product Description HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.

Short Description Stainless Steel Tie, 14.3" Long, 202lb Tensile Strength, SS316, Metal, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 202.0 lbs

Minimum Tensile Strength (Metric) 900.0 N

Length L (Imperial) 14.3 "

Length L (Metric) 362.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure ball bearing lock

Variant No Serration

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Bundle Diameter Min. (Imperial) 0.47 "

Bundle Diameter Min. (Metric) 12.0 mm

Bundle Diameter Max. (Imperial) 4.0 "

Bundle Diameter Max. (Metric) 102.0 mm

Thickness T (Imperial) 0.01 "

Thickness T (Metric) 0.3 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 4000 Pieces

Material and Specifications

Material	Stainless Steel (SS316)
Material Shortcut	SS316
Flammability	non-burning
Halogenfree	Yes
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
ROHS Compliant	Yes
Certification/Specification	ABS Det Norske Veritas BV GL