

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP6010C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

SNP6010C2



Article Number: 190-00196

Snapper Hose Clamps, 2.259"/2.582" Min/Max Diameter, POM, White, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SNP6010C2

Type SNP60

Color White (WH)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, 2.259"/2.582" Min/Max Diameter, POM, White, 100/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.291 "

Width W2 (Metric) 7.39 mm

Bundle Diameter Min. (Imperial) 2.28 "

Bundle Diameter Min. (Metric) 58.0 mm

Bundle Diameter Max. (Imperial) 2.52 "

Bundle Diameter Max. (Metric) 64 mm

Diameter Min. (Imperial) 2.259 "

Diameter Min. (Metric) 57.38 mm

Diameter Max. (Imperial) 2.582 "

Diameter Max. (Metric) 65.58 mm

Wall Thickness WT (Imperial) 0.067 "

Wall Thickness WT (Metric) 1.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 500

Material and Specifications

Material Polyacetal (POM)



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP6010C2 - SNAPPER HOSE CLAMP WHITE

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Flammability UL94 HB

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes