

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[4FRP9C](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

4FRP9C



Article Number: 161-05058

Spiralwrap, 3/4" Diameter, PE-FR, Natural, 100ft/RL



Download spec sheet

Base Data

Local Order Number 4FRP9C

Type 4FRP

Color Natural (NA)

Features and Benefits

- Sheathing allows flexible routing and lead-out of cables
- The inner edges are beveled preventing damage to cables
- Sheathing is reusable and resistant to most chemicals
- Spiralwrap is U.L. Recognized

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

Short Description Spiralwrap, 3/4" Diameter, PE-FR, Natural, 100ft/RL

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Variant Spiral Binding

Bundle Diameter Min. (Imperial) 0.75 "

Bundle Diameter Min. (Metric) 19.05 mm

Bundle Diameter Max. (Imperial) 5.0 "

Bundle Diameter Max. (Metric) 127.0 mm

Diameter D (imperial) 0.75 "

Diameter D (metric) 19.05 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.05 mm

Wall Thickness WT (Imperial) 0.065 "

Wall Thickness WT (Metric) 1.65 mm

Pitch (imperial) 0.75 "

Pitch (metric) 19.05 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100.0 ft

Package Quantity (Metric) 30.48 m

Material and Specifications

Material	Polyethylene, flame retardant (PE-FR)
Material Shortcut	PE-FR
Flammability	UL94 V2
Operating Temperature	-4°F to +176°F (-20°C to +80°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes