



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 117-00012 - STD OFF DL CLMP 100LB .31"DIA BK

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[117-00012](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

117-00012

Article Number: 117-00012

Stand Off Dual Clamp Tie, 20.1" Length, 0.31" Stud Dia., PA66HIRHSUV, Black, 150/pkg



Download spec sheet

Base Data

Local Order Number 117-00012

Type SDCTR312

Color Black (BK)

- Features and Benefits**
- Wide strap minimizes pinching of soft hoses and convoluted tubing.
 - Clamping rails increase circumferential grip on varying bundle diameters.
 - Locking stud mount pawls allow for easy hand insertion.
 - Nut or weld nesting counterbore provides flush mounting at the base.

Product Description Stand Off Dual Clamp Ties offer the same features as the standard dual clamp tie, with a standoff mount that secures the bundle away from the side of the frame rail. This protects the bundles from bolts and other protrusions.

Short Description Stand Off Dual Clamp Tie, 20.1" Length, 0.31" Stud Dia., PA66HIRHSUV, Black, 150/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 100.0 lbs

Minimum Tensile Strength (Metric) 445.0 N

Length L (Imperial) 20.1 "

Length L (Metric) 510.5 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Height H (Imperial) 1.47 "

Height H (Metric) 37.3 mm

Bundle Diameter Min. (Imperial) 0.375 "

Bundle Diameter Min. (Metric) 9.5 mm

Bundle Diameter Max. (Imperial) 2.3 "

Bundle Diameter Max. (Metric) 58.4 mm

Stud Size (Imperial) 0.313 "

Stud Size (Metric) 8.0 mm

Logistics and Packaging

Quantity Per carton



Carton Quantity 150

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes