



Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[156-00066](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

156-00066



Article Number: 156-00066

Fir Tree with Tie, 15.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00066

Type T50LFT6

Color Black (BK)

- Features and Benefits**
- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
 - Initial fir tree serves as a locating feature for assistance in blind assembly applications.
 - Disc feature provides anti-rattle protection in high vibration applications.

Product Description Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

Short Description Fir Tree with Tie, 15.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 15.0 "

Length L (Metric) 390.0 mm

Length L2 (Imperial) 0.46 "

Length L2 (Metric) 11.6 mm

Length L3 (imperial) 0.54 "

Length L3 (metric) 13.8 mm

Fixation Method Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.6 mm

Width W2 (Imperial) 0.35 "

Width W2 (Metric) 9.0 mm

Width W3 (Imperial) 0.2 "

Width W3 (Metric) 5.0 mm

Height H (Imperial) 0.05 "

Height H (Metric) 1.2 mm

Height H2 (Imperial) 0.3 "

Bundle Diameter Min. (Imperial)	0.06 "		
Bundle Diameter Min. (Metric)	4.0 mm		
Bundle Diameter Max. (Imperial)	4.3 "		
Bundle Diameter Max. (Metric)	110 mm		
Disc Diameter (Imperial)	0.63 "		
Disc Diameter (Metric)	16.0 mm		
Panel Thickness Max. (Imperial)	0.12 "		
Panel Thickness Max. (Metric)	3.0 mm		
Panel Thickness Min. (Imperial)	0.03 "		
Panel Thickness Min. (Metric)	0.75 mm		
Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm		
Mounting Hole Diameter D Min. (Imperial)	0.252 "		
		Mounting Hole Diameter D Max.0.28 "	
		(Imperial)	Mounting Hole Diameter D Max.7.0 mm
			(Metric)6.5 mm
Mounting Hole Diameter D Min. (Metric)			
Thickness T (Metric)	1.2 mm		

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500
Carton Quantity	1500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes