

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[MB4SHA10H4](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## MB4SHA10H4



**Article Number:** 151-29206

**Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg**



Download spec sheet

### Base Data

**Local Order Number** MB4SHA10H4

**Type** MB4SHA

**Color** White (WH)

**Features and Benefits**

- 2-way opening for use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Secures using the adhesive backing and/or with one screw.

**Product Description** HellermannTyton's 2 way, adhesive fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by inserting one screw through the center of the mount.

**Short Description** Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg

### Product Dimensions

**Length L (Imperial)** 1.12 "

**Length L (Metric)** 28.3 mm

**Fixation Method** Screw Mounting and Adhesive

**Width W (Imperial)** 1.12 "

**Width W (Metric)** 28.3 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.6 mm

**Height H (Imperial)** 0.23 "

**Height H (Metric)** 5.8 mm

**Mounting Hole Diameter D (Imperial)** 0.15 "

**Mounting Hole Diameter D (Metric)** 3.9 mm

**Thickness of Adhesive TA (Imperial)** 0.031 "

**Mounting Hole Diameter D Max.** 3.9 mm

**(Metric) Mounting Hole Diameter D Min. (Metric)** 3.9 mm

**Thickness of Adhesive TA (Metric)** 0.8 mm

### Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500

**Carton Quantity** 4000

### Material and Specifications

**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**Adhesive Shortcut** Synthetic rubber T50

**Adhesive Operating Temperature** -4°F to +122°F (-20°C to +50°C)

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes