

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[REL50L0L4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

REL50L0L4



Article Number: 115-00602

Releasable Cable Tie, 9.8" Long, 50 lb Tensile Strength, PA66, Black, 200/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number REL50L0L4

Type REL50L

Color Black (BK)

Features and Benefits

- Special design offers a release feature for quick and easy access to wire bundles.
- Head design provides high tensile strength even after repeated use; providing additional longevity.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Releasable Cable Tie, 9.8" Long, 50 lb Tensile Strength, PA66, Black, 200/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225.0 N

Length L (Imperial) 9.8 "

Length L (Metric) 250 mm

Fixation Method None

Identification Plate Position none

Releasable Closure Yes

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.4 mm

Cable Tie Width Max. (Imperial) 0.42 "

Cable Tie Width Max. (Metric) 10.7 mm

Height H2 (Imperial) 0.31 "

Height H2 (Metric) 7.8 mm

Bundle Diameter Min. (Imperial) 0.1 "

Bundle Diameter Min. (Metric) 2.5 mm

Bundle Diameter Max. (Imperial) 2.8 "

Bundle Diameter Max. (Metric) 70.0 mm

Logistics and Packaging

Quantity Per bag



Carton Quantity 5000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes