

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[RTT750HR.NX900](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

RTT750HR.NX900



Article Number: 115-00001

Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg



Download spec sheet

Base Data

Local Order Number RTT750HR.NX900

Type SpeedyTie (RTT750HR)

Color Red (RD)
Yellow (YE)

Features and Benefits

- The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.
- Additional design feature on the head allows excess strap to be tucked away after installation.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

Short Description Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 200.0 lbs

Minimum Tensile Strength (Metric) 888.0 N

Length L (Imperial) 29.6 "

Length L (Metric) 752.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure Yes

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.51 "

Width W (Metric) 13.0 mm

Bundle Diameter Min. (Imperial) 1.6 "

Bundle Diameter Min. (Metric) 40.0 mm

Bundle Diameter Max. (Imperial) 8.3 "

Bundle Diameter Max. (Metric) 210 mm

Thickness T (Imperial) 0.075 "

Thickness T (Metric) 1.9 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 5 Pieces



Carton Quantity 60 Pieces

Weight (Metric) 23.2 kg

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes