

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T120L9K2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T120L9K2



Article Number: 111-12419

Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg



Download spec sheet

Base Data

Local Order Number T120L9K2

Type T120L

Color Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66, Natural, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 535.0 N

Length L (Imperial) 30.0 "

Length L (Metric) 760.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.6 mm

Bundle Diameter Min. (Imperial) 0.23 "

Bundle Diameter Min. (Metric) 5.76 mm

Bundle Diameter Max. (Imperial) 8.85 "

Bundle Diameter Max. (Metric) 225.0 mm

Thickness T (Imperial) 0.075 "

Cable Tie Head Length (Imperial) 0.393 "

Cable Tie Head Width (Imperial) 0.502 "

Thickness T (Metric) 1.9 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	50
Carton Quantity	1000
Weight (Metric)	11.5 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MILSPEC	MS3367-6-9
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	SAE - AS33671 UL-ZODZ E64139 Cage Code 53421
UL Listed (US and Canada)	Yes
UL Recognized (US and Canada)	Yes