

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T120L0UVK2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T120L0UVK2



**Article Number:** 111-12460

**Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66UV, Black, 50/pkg**



Download spec sheet

### Base Data

**Local Order Number** T120L0UVK2

**Type** T120L

**Color** Black (BK)

**Features and Benefits**

- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures .
- Head design provides high tensile strength with very low insertion force.
- Bent tail ensures a quick and simple installation.

**Product Description** HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Heavy Duty Cable Tie, 30" Long, 120lb Tensile Strength, PA66UV, Black, 50/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 535.0 N

**Length L (Imperial)** 30.0 "

**Length L (Metric)** 760.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.3 "

**Width W (Metric)** 7.6 mm

**Bundle Diameter Min. (Imperial)** 0.23 "

**Bundle Diameter Min. (Metric)** 5.76 mm

**Bundle Diameter Max. (Imperial)** 8.85 "

**Bundle Diameter Max. (Metric)** 225.0 mm

**Thickness T (Imperial)** 0.075 "

**Cable Tie Head Length (Imperial)** 0.393 "

**Cable Tie Head Width (Imperial)** 0.502 "

**Thickness T (Metric)** 1.9 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	50
<b>Carton Quantity</b>	1000 Pieces
<b>Weight (Metric)</b>	11.5 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Material Shortcut</b>	PA66UV
<b>US MILSPEC</b>	MS3367-6-0
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-ZODZ2.E64139 SAE - AS33671 Cage Code 53421
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No