

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T30RSF9C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T30RSF9C2



Article Number: 111-85603

Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T30RSF9C2

Type T30RSF(U)

Color Natural (NA)

- Features and Benefits**
- Push Mount design provides quick and easy mounting.
 - Push mount style creates low insertion and high extraction force.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6.3" Long, 30lb Tensile, Panel Thickness 0.19"- 0.22", PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 136 N

Length L (Imperial) 6.3 "

Length L (Metric) 158.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14 "

Width W (Metric) 3.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.8 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 32.0 mm

Panel Thickness Max. (Imperial) 0.09 "

Panel Thickness Max. (Metric) 2.1 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 0.75 mm

Mounting Hole Diameter D (Imperial) 0.19 - 0.22 "

Mounting Hole Diameter D (Metric) 4.7 - 5.5 mm

Mounting Hole Diameter D Min. (Imperial)	0.19 "	Mounting Hole Diameter D Max. (Imperial)	0.22 "	Thickness T (Imperial)	0.05 "
Mounting Hole Diameter D Max. (Metric)	5.6 mm	Mounting Hole Diameter D Min. (Metric)	4.7 mm		
Thickness T (Metric)	1.2 mm				

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100 Pieces
Carton Quantity	5000 Pieces
Weight (Metric)	0.9 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes