

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[IXYS Corporation](#)
[MDMA85P1600TG](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

Standard Rectifier Module

$$V_{RRM} = 2 \times 1600V$$


$$I_{FAV} = 85A$$

$$V_F = 1.1V$$


Phase leg


Part number

MDMA85P1600TG



Backside: isolated

 E72873



Features / Advantages:

- Package with DCB ceramic
- Improved temperature and power cycling
- Planar passivated chips
- Very low forward voltage drop
- Very low leakage current

Applications:


- Diode for main rectification
- For single and three phase bridge configurations
- Supplies for DC power equipment
- Input rectifiers for PWM inverter
- Battery DC power supplies
- Field supply for DC motors

Package: TO-240AA

- Isolation Voltage: 4800 V~
- Industry standard outline
- RoHS compliant
- Height: 30 mm
- Base plate: DCB ceramic
- Reduced weight
- Advanced power cycling

| Rectifier | | | | Ratings | | | |
|------------|--|--|------------------------------|---------|------|---------------|-------------------|
| Symbol | Definition | Conditions | min. | typ. | max. | Unit | |
| V_{RSM} | max. non-repetitive reverse blocking voltage | | | | 1700 | V | |
| V_{RRM} | max. repetitive reverse blocking voltage | | | | 1600 | V | |
| I_R | reverse current | $V_R = 1600\text{ V}$ | | | 100 | μA | |
| | | $V_R = 1600\text{ V}$ | | | 2 | mA | |
| V_F | forward voltage drop | $I_F = 85\text{ A}$ | | | 1.15 | V | |
| | | $I_F = 170\text{ A}$ | | | 1.38 | V | |
| | | $I_F = 85\text{ A}$ | $T_{VJ} = 125^\circ\text{C}$ | | | 1.10 | V |
| | | $I_F = 170\text{ A}$ | | | | 1.39 | V |
| I_{FAV} | average forward current | $T_C = 100^\circ\text{C}$ rectangular $d = 0.5$ | | | 85 | A | |
| V_{F0} | threshold voltage | } for power loss calculation only | | | 0.79 | V | |
| r_F | slope resistance | | | | 3.5 | m Ω | |
| R_{thJC} | thermal resistance junction to case | | | | 0.35 | K/W | |
| R_{thCH} | thermal resistance case to heatsink | | | 0.20 | | K/W | |
| P_{tot} | total power dissipation | | | | 350 | W | |
| I_{FSM} | max. forward surge current | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$ | $T_{VJ} = 45^\circ\text{C}$ | | | 1.50 | kA |
| | | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$ | $V_R = 0\text{ V}$ | | | 1.62 | kA |
| | | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$ | $T_{VJ} = 150^\circ\text{C}$ | | | 1.28 | kA |
| | | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$ | $V_R = 0\text{ V}$ | | | 1.38 | kA |
| I^2t | value for fusing | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$ | $T_{VJ} = 45^\circ\text{C}$ | | | 11.3 | kA ² s |
| | | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$ | $V_R = 0\text{ V}$ | | | 10.9 | kA ² s |
| | | $t = 10\text{ ms}; (50\text{ Hz}), \text{ sine}$ | $T_{VJ} = 150^\circ\text{C}$ | | | 8.13 | kA ² s |
| | | $t = 8,3\text{ ms}; (60\text{ Hz}), \text{ sine}$ | $V_R = 0\text{ V}$ | | | 7.87 | kA ² s |
| C_J | junction capacitance | $V_R = 400\text{ V}; f = 1\text{ MHz}$ | | | 60 | pF | |

| Package TO-240AA | | | | Ratings | | | |
|------------------|--|----------------------|-------------------------------------|---------|------|------|------|
| Symbol | Definition | Conditions | | min. | typ. | max. | Unit |
| I_{RMS} | RMS current | per terminal | | | | 200 | A |
| T_{VJ} | virtual junction temperature | | | -40 | | 150 | °C |
| T_{op} | operation temperature | | | -40 | | 125 | °C |
| T_{stg} | storage temperature | | | -40 | | 125 | °C |
| Weight | | | | | 90 | | g |
| M_D | mounting torque | | | 2.5 | | 4 | Nm |
| M_T | terminal torque | | | 2.5 | | 4 | Nm |
| $d_{Spp/App}$ | creepage distance on surface striking distance through air | terminal to terminal | 13.0 | 9.7 | | | mm |
| $d_{Spb/Apb}$ | | terminal to backside | 16.0 | 16.0 | | | mm |
| V_{ISOL} | isolation voltage | t = 1 second | 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA | 4800 | | | V |
| | | t = 1 minute | | 4000 | | | V |



Part number


- M = Module
- D = Diode
- M = Standard Rectifier
- A = (up to 1800V)
- 85 = Current Rating [A]
- P = Phase leg
- 1600 = Reverse Voltage [V]
- TG = TO-240AA

| Ordering | Part Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|---------------|--------------------|---------------|----------|----------|
| Standard | MDMA85P1600TG | MDMA85P1600TG | Box | 6 | 513008 |

Equivalent Circuits for Simulation

* on die level




$T_{VJ} = 150^\circ\text{C}$



Rectifier

| | | | |
|-------------|--------------------|------|----|
| $V_{0\max}$ | threshold voltage | 0.79 | V |
| $R_{0\max}$ | slope resistance * | 2.3 | mΩ |

Outlines TO-240AA



Rectifier




Fig. 1 Forward current versus voltage drop per diode




Fig. 2 Surge overload current vs. time per diode




Fig. 3 I^2t versus time per diode




Fig. 4 Power dissipation vs. forward current and ambient temperature per diode




Fig. 5 Max. forward current vs. case temperature per diode




Fig. 6 Transient thermal impedance junction to case vs. time per diode

Constants for Z_{thJC} calculation:

| i | R_{thi} (K/W) | t_i (s) |
|---|-----------------|-----------|
| 1 | 0.012 | 0.001 |
| 2 | 0.048 | 0.013 |
| 3 | 0.185 | 0.070 |
| 4 | 0.105 | 0.400 |