

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[A-TB500-HA02H](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

	1	2	3	4	5	6	7																																																																																	
A					<p><b>Material</b></p> <ul style="list-style-type: none"> <li>① Terminal body(Contact pin): Brass</li> <li>② Wire guard: Stainless steel</li> <li>③ Surface of solder tail: Tin plated</li> <li>④ Insulator(housing): Thermoplastic (UL94V-0), GREEN(RAL6018/T)</li> </ul> <p><b>Electrical</b>      cULus/VDE</p> <p>Voltage rating: 300VAC/250VAC            Current rating: 10A/10A            Wire range: 0.75-1.5mm<sup>2</sup>            Solid wire(AWG): 14-24            Stranded wire(AWG): 14-24            Pull force:            Screw:            Wire strip length: 9-10mm            Withstanding Voltage: 1.6KV/2KV            Operating temperature: -40°C to +115°C            Soldering temperature: 250°C±10°C/5 Sec            Safety Approval:  </p>			A																																																																																
B								B																																																																																
C								C																																																																																
D								D																																																																																
E								E																																																																																
F	<p>RECOMMENDER PCB LAYOUT</p>				<p><b>DIMENSION</b></p> <table border="1"> <tr> <td>L</td> <td>Nx5.0</td> </tr> <tr> <td>P</td> <td>(N-1)x5.0</td> </tr> </table> <p>N=Number of poles</p> <table border="1"> <thead> <tr> <th rowspan="2">Poles</th> <th colspan="2">Tolerance</th> </tr> <tr> <th>DIM L</th> <th>DIM P</th> </tr> </thead> <tbody> <tr> <td>2p-6p</td> <td>±0.20</td> <td>±0.20</td> </tr> <tr> <td>7p-12p</td> <td>±0.25</td> <td>±0.25</td> </tr> <tr> <td>13p-24p</td> <td>±0.40</td> <td>±0.40</td> </tr> </tbody> </table>			L	Nx5.0	P	(N-1)x5.0	Poles	Tolerance		DIM L	DIM P	2p-6p	±0.20	±0.20	7p-12p	±0.25	±0.25	13p-24p	±0.40	±0.40	F																																																														
L	Nx5.0																																																																																							
P	(N-1)x5.0																																																																																							
Poles	Tolerance																																																																																							
	DIM L	DIM P																																																																																						
2p-6p	±0.20	±0.20																																																																																						
7p-12p	±0.25	±0.25																																																																																						
13p-24p	±0.40	±0.40																																																																																						
G	<p><b>RoHS compliant</b> Unit: mm</p>				<table border="1"> <tr> <td>Scale</td> <td>Free</td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td colspan="8">TOLERANCE</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td>Approved</td> <td>16.04.2013</td> <td>Amy</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="8">DIM TOL</td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td>①</td> <td>Update</td> <td>16.04.2013</td> <td>Amy</td> <td colspan="2">ASSMANN WSW-No. <b>A-TB500-HAxxH</b></td> </tr> <tr> <td colspan="8">Angle TOL</td> </tr> <tr> <td></td> <td></td> <td>②</td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> <td colspan="2">Drawing-No. <b>ASS 4125 CO</b>    rev01</td> </tr> <tr> <td></td> <td></td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="2">Replace      Sheet</td> </tr> </table>			Scale	Free				Date	Name	Customer-No.	TOLERANCE								X.	±0.50				Drawn	19.04.2010	Alex	X.X	±0.30				Approved	16.04.2013	Amy	X.XX	±0.10							DIM TOL								X.°	±1°	①	Update	16.04.2013	Amy	ASSMANN WSW-No. <b>A-TB500-HAxxH</b>		Angle TOL										②	Drawn	19.04.2010	Alex	Drawing-No. <b>ASS 4125 CO</b> rev01				Id.	Modification	Date	Name	Replace      Sheet		G
Scale	Free				Date	Name	Customer-No.																																																																																	
TOLERANCE																																																																																								
X.	±0.50				Drawn	19.04.2010	Alex																																																																																	
X.X	±0.30				Approved	16.04.2013	Amy																																																																																	
X.XX	±0.10																																																																																							
DIM TOL																																																																																								
X.°	±1°	①	Update	16.04.2013	Amy	ASSMANN WSW-No. <b>A-TB500-HAxxH</b>																																																																																		
Angle TOL																																																																																								
		②	Drawn	19.04.2010	Alex	Drawing-No. <b>ASS 4125 CO</b> rev01																																																																																		
		Id.	Modification	Date	Name	Replace      Sheet																																																																																		
H								H																																																																																
	1	2	3	4	5	6	7																																																																																	