

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[A-TB500-HA02V](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																																																									
A					<p>Material</p> <p>Terminal body(Contact pin): Brass Wire guard:Stainless steel Surface of Solder tail:Tin plated Terminal (housing): Thermoplastic (UL94V-0) , GREEN(RAL6018/T)</p>				A																																																																							
B									B																																																																							
C					<p>Electrical cULus/VDE</p> <p>Voltage rating: 300VAC/250VAC Current rating: 10A/10A Wire range: 0.75-1.5mm² Solid wire(AWG): 14-24 Stranded wire(AWG): 14-24 Pull force: Screw: Wire strip length: 9-10mm Withstanding Voltage: 1.6KV/2KV Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval: </p>				C																																																																							
D									D																																																																							
E					<p>DIMENSION</p> <table border="1"> <tr> <td>L</td> <td>Nx5.0</td> </tr> <tr> <td>P</td> <td>(N-1)x5.0</td> </tr> </table> <p>N=Number of poles</p>		L	Nx5.0	P	(N-1)x5.0	<table border="1"> <thead> <tr> <th rowspan="2">Poles</th> <th colspan="2">Tolerance</th> </tr> <tr> <th>DIM L</th> <th>DIM P</th> </tr> </thead> <tbody> <tr> <td>2p-6p</td> <td>±0.20</td> <td>±0.20</td> </tr> <tr> <td>7p-12p</td> <td>±0.25</td> <td>±0.25</td> </tr> <tr> <td>13p-24p</td> <td>±0.40</td> <td>±0.40</td> </tr> </tbody> </table>		Poles	Tolerance		DIM L	DIM P	2p-6p	±0.20	±0.20	7p-12p	±0.25	±0.25	13p-24p	±0.40	±0.40	E																																																					
L	Nx5.0																																																																															
P	(N-1)x5.0																																																																															
Poles	Tolerance																																																																															
	DIM L	DIM P																																																																														
2p-6p	±0.20	±0.20																																																																														
7p-12p	±0.25	±0.25																																																																														
13p-24p	±0.40	±0.40																																																																														
F									F																																																																							
G	<p>RoHS compliant Unit: mm</p>		<p>RECOMMENDER PCB LAYOUT</p> <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th></th> <th></th> <th></th> <th></th> <th>Date</th> <th>Name</th> <th>Customer-No.</th> </tr> </thead> <tbody> <tr> <td colspan="9">TOLERANCE</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td>Approved</td> <td>17.04.2013</td> <td>Amy</td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>①</td> <td>Update</td> <td>17.04.2013</td> <td>Amy</td> <td colspan="3" rowspan="2"> </td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td>②</td> <td>Drawn</td> <td>19.04.2010</td> <td>Alex</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="3"> <table border="1"> <thead> <tr> <th>Replace</th> <th>Sheet</th> </tr> </thead> <tbody> <tr> <td>ASS 4119 CO</td> <td>rev01</td> </tr> </tbody> </table> </td> </tr> </tbody> </table>		Scale	Free					Date	Name	Customer-No.	TOLERANCE									X.	±0.50					Drawn	19.04.2010	Alex	X.X	±0.30					Approved	17.04.2013	Amy	X.XX	±0.10								DIM	TOL	①	Update	17.04.2013	Amy				X.°	±1°	②	Drawn	19.04.2010	Alex	Angle	TOL	Id.	Modification	Date	Name	<table border="1"> <thead> <tr> <th>Replace</th> <th>Sheet</th> </tr> </thead> <tbody> <tr> <td>ASS 4119 CO</td> <td>rev01</td> </tr> </tbody> </table>			Replace	Sheet	ASS 4119 CO	rev01			G
Scale	Free					Date	Name	Customer-No.																																																																								
TOLERANCE																																																																																
X.	±0.50					Drawn	19.04.2010	Alex																																																																								
X.X	±0.30					Approved	17.04.2013	Amy																																																																								
X.XX	±0.10																																																																															
DIM	TOL	①	Update	17.04.2013	Amy																																																																											
X.°	±1°	②	Drawn	19.04.2010	Alex																																																																											
Angle	TOL	Id.	Modification	Date	Name	<table border="1"> <thead> <tr> <th>Replace</th> <th>Sheet</th> </tr> </thead> <tbody> <tr> <td>ASS 4119 CO</td> <td>rev01</td> </tr> </tbody> </table>			Replace	Sheet	ASS 4119 CO	rev01																																																																				
Replace	Sheet																																																																															
ASS 4119 CO	rev01																																																																															
H									H																																																																							
	1	2	3	4	5	6	7																																																																									