

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[ASSMANN WSW Components](#)

[A-TB500-VY02](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

	1	2	3	4	5	6	7																																																																					
A			<p>RECOMMENDED PCB LAYOUT</p>		<p>Material</p> <p>Item ① Terminal body(metal housing): Brass(CuZn),Tin plated Item ② Terminal screw: Steel Zinc plating "-" slot type Item ③ Wire guard: Stainless steel Item ④ Insulator (housing): Thermoplastic(UL94V-0),Black</p> <p>Electrical</p> <p>Voltage rating: 300VAC Current rating: 15A Wire range: Solid wire(AWG): 14-22 Stranded wire(AWG): 14-22 Torque(Lb-In): 3.5 Screw: M2.6 Wire strip length: 6-7mm Withstanding Voltage: 1.6KV Operating temperature: -40°C to +115°C Soldering temperature: 250°C±10°C/5 Sec Safety Approval: </p>			A																																																																				
B								B																																																																				
C								C																																																																				
D								D																																																																				
E	<p>N=NUMBER OF CONTACTS</p>				<p>N=Number of poles L=Nx5,0 P=(N-1)x5,0</p> <p>TOL</p> <table border="1"> <thead> <tr> <th>POLES</th> <th>L</th> <th>P</th> </tr> </thead> <tbody> <tr> <td>2p-6p</td> <td>±0,20</td> <td>±0,15</td> </tr> <tr> <td>7p-12p</td> <td>±0,25</td> <td>±0,20</td> </tr> <tr> <td>13p-18p</td> <td>±0,30</td> <td>±0,25</td> </tr> <tr> <td>19p-24p</td> <td>±0,40</td> <td>±0,30</td> </tr> </tbody> </table>			POLES	L	P	2p-6p	±0,20	±0,15	7p-12p	±0,25	±0,20	13p-18p	±0,30	±0,25	19p-24p	±0,40	±0,30	E																																																					
POLES	L	P																																																																										
2p-6p	±0,20	±0,15																																																																										
7p-12p	±0,25	±0,20																																																																										
13p-18p	±0,30	±0,25																																																																										
19p-24p	±0,40	±0,30																																																																										
F								F																																																																				
G	<p>RoHS compliant</p>		<table border="1"> <tr> <td>Scale</td> <td>1:1</td> <td></td> <td></td> <td></td> <td></td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td>TOLERANCE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td>14.09.2007</td> <td>Dean</td> </tr> <tr> <td>X.</td> <td>±0.50</td> <td></td> <td></td> <td></td> <td></td> <td>Approved</td> <td>20.04.2010</td> <td>Hellwig</td> </tr> <tr> <td>X.X</td> <td>±0.30</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>X.XX</td> <td>±0.10</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>②</td> <td>Update</td> <td>20.04.2010</td> <td>Dean</td> <td colspan="3" rowspan="2"> </td> </tr> <tr> <td>X.°</td> <td>±1°</td> <td>①</td> <td>Drawn</td> <td>14.09.2007</td> <td>Hellwig</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td>Replace</td> <td>Sheet</td> <td></td> </tr> </table>		Scale	1:1					Date	Name	Customer-No.	TOLERANCE						Drawn	14.09.2007	Dean	X.	±0.50					Approved	20.04.2010	Hellwig	X.X	±0.30								X.XX	±0.10								DIM	TOL	②	Update	20.04.2010	Dean				X.°	±1°	①	Drawn	14.09.2007	Hellwig	Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet		<p>ASSMANN WSW-No. A-TB500-VYxx</p> <p>Drawing-No. ASS 2336 CO rev02</p>		G
Scale	1:1					Date	Name	Customer-No.																																																																				
TOLERANCE						Drawn	14.09.2007	Dean																																																																				
X.	±0.50					Approved	20.04.2010	Hellwig																																																																				
X.X	±0.30																																																																											
X.XX	±0.10																																																																											
DIM	TOL	②	Update	20.04.2010	Dean																																																																							
X.°	±1°	①	Drawn	14.09.2007	Hellwig																																																																							
Angle	TOL	Id.	Modification	Date	Name	Replace	Sheet																																																																					
H								H																																																																				
	1	2	3	4	5	6	7	SV523																																																																				