

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)
[09180647005](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

Alle Rechte vorbehalten/ All rights reserved

5	4	3	2	1																																																																				
D																																																																								
C	<table style="width:100%; border: none;"> <tr> <td style="width: 30%;">Wire _____</td> <td style="width: 30%;">Cu tinned</td> <td style="width: 10%;"></td> <td style="width: 30%;"></td> </tr> <tr> <td>Gauge _____</td> <td>AWG 28/7</td> <td></td> <td></td> </tr> <tr> <td>Voltage rating _____</td> <td>300 Vr.m.s</td> <td></td> <td></td> </tr> <tr> <td>Current (Max) _____</td> <td>2,1A at 25°</td> <td></td> <td style="text-align: center;">Colour code sequence (in 10 steps):</td> </tr> <tr> <td>Conductor resistance _____</td> <td>221 mΩ/m</td> <td></td> <td style="text-align: center;">-brown</td> </tr> <tr> <td>Capacity unbalanced _____</td> <td>42,7 pF/m</td> <td></td> <td style="text-align: center;">-red</td> </tr> <tr> <td>Impedance unbalanced _____</td> <td>105 Ω</td> <td></td> <td style="text-align: center;">-orange</td> </tr> <tr> <td>Inductance unbalanced _____</td> <td>0,68 μH/m</td> <td></td> <td style="text-align: center;">-yellow</td> </tr> <tr> <td>Signal delay _____</td> <td>4,9 ns/m</td> <td></td> <td style="text-align: center;">-green</td> </tr> <tr> <td>Insulation material _____</td> <td>PVC</td> <td></td> <td style="text-align: center;">-blue</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">-violet</td> </tr> <tr> <td>Temperature rating _____</td> <td>-20°C (operating) to 105°C</td> <td></td> <td style="text-align: center;">-grey</td> </tr> <tr> <td></td> <td>-30°C (static)</td> <td></td> <td style="text-align: center;">-white</td> </tr> <tr> <td>Flammability rating _____</td> <td>UL: VW1</td> <td></td> <td style="text-align: center;">-black</td> </tr> <tr> <td>Insulation resistance _____</td> <td>100 MΩ/km</td> <td></td> <td></td> </tr> <tr> <td>Approval _____</td> <td>UL AWM style 2651</td> <td></td> <td></td> </tr> </table>				Wire _____	Cu tinned			Gauge _____	AWG 28/7			Voltage rating _____	300 Vr.m.s			Current (Max) _____	2,1A at 25°		Colour code sequence (in 10 steps):	Conductor resistance _____	221 mΩ/m		-brown	Capacity unbalanced _____	42,7 pF/m		-red	Impedance unbalanced _____	105 Ω		-orange	Inductance unbalanced _____	0,68 μH/m		-yellow	Signal delay _____	4,9 ns/m		-green	Insulation material _____	PVC		-blue				-violet	Temperature rating _____	-20°C (operating) to 105°C		-grey		-30°C (static)		-white	Flammability rating _____	UL: VW1		-black	Insulation resistance _____	100 MΩ/km			Approval _____	UL AWM style 2651						
Wire _____	Cu tinned																																																																							
Gauge _____	AWG 28/7																																																																							
Voltage rating _____	300 Vr.m.s																																																																							
Current (Max) _____	2,1A at 25°		Colour code sequence (in 10 steps):																																																																					
Conductor resistance _____	221 mΩ/m		-brown																																																																					
Capacity unbalanced _____	42,7 pF/m		-red																																																																					
Impedance unbalanced _____	105 Ω		-orange																																																																					
Inductance unbalanced _____	0,68 μH/m		-yellow																																																																					
Signal delay _____	4,9 ns/m		-green																																																																					
Insulation material _____	PVC		-blue																																																																					
			-violet																																																																					
Temperature rating _____	-20°C (operating) to 105°C		-grey																																																																					
	-30°C (static)		-white																																																																					
Flammability rating _____	UL: VW1		-black																																																																					
Insulation resistance _____	100 MΩ/km																																																																							
Approval _____	UL AWM style 2651																																																																							
A	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%;"></td> <td style="width: 10%; text-align: center;">Det.</td> <td style="width: 10%; text-align: center;">Name</td> <td rowspan="4" style="text-align: center;"> All Dim. in mm Orig. Size DIN A 4 </td> <td style="width: 20%; text-align: center;">SEK 18 Flat cable</td> <td style="width: 10%; text-align: center;">Majstab/ Scale</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Detail.</td> <td style="text-align: center;">20/10/05</td> <td style="text-align: center;">JMDR</td> <td rowspan="2" style="text-align: center;">64 poles, lenght per reel: 30,48 m IEC 918</td> <td style="text-align: center;">10:1</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Insp.</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">Stand.</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">EC01446</td> <td style="text-align: center;">22/02/10</td> <td style="text-align: center;">SC</td> <td colspan="2" style="text-align: center;">HARTING EURL F-95972 Paris</td> <td style="text-align: center;"></td> <td style="text-align: center;">TB 09 18 064 7005</td> <td style="text-align: center;">Blatt/ Page</td> </tr> <tr> <td></td> <td style="text-align: center;">33990</td> <td style="text-align: center;">14/05/07</td> <td style="text-align: center;">PK</td> <td colspan="2"></td> <td></td> <td style="text-align: center;">Sub.</td> <td style="text-align: center;">1 / 1</td> </tr> <tr> <td></td> <td style="text-align: center;">33246</td> <td style="text-align: center;">20/10/05</td> <td style="text-align: center;">JMDR</td> <td colspan="2"></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Mod.</td> <td style="text-align: center;">Det.</td> <td style="text-align: center;">Name</td> <td colspan="2"></td> <td></td> <td></td> <td></td> </tr> </table>							Det.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 Flat cable	Majstab/ Scale				Detail.	20/10/05	JMDR	64 poles, lenght per reel: 30,48 m IEC 918	10:1				Insp.								Stand.						EC01446	22/02/10	SC	HARTING EURL F-95972 Paris			TB 09 18 064 7005	Blatt/ Page		33990	14/05/07	PK				Sub.	1 / 1		33246	20/10/05	JMDR							Mod.	Det.	Name					
			Det.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 Flat cable	Majstab/ Scale																																																																	
			Detail.	20/10/05		JMDR	64 poles, lenght per reel: 30,48 m IEC 918	10:1																																																																
			Insp.																																																																					
			Stand.																																																																					
	EC01446	22/02/10	SC	HARTING EURL F-95972 Paris			TB 09 18 064 7005	Blatt/ Page																																																																
	33990	14/05/07	PK				Sub.	1 / 1																																																																
	33246	20/10/05	JMDR																																																																					
	Mod.	Det.	Name																																																																					