

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Harting](#)
[09451451300](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

1	2	3	4	5	6																																										
A																																															
B																																															
C																																															
D	<p>x3 Stamped power crimp contact : for stranded wire AWG 20-24 with Ø maxi.1.52 mm. x4 Stamped data crimp contact : for stranded wire AWG 24-26 with Ø maxi.1.38 mm. Plating : mini. Au 0.76 µm over nickel.</p> <p>Set of codings keys.</p> <p>Set of sealing glands: for 4.9 to 6.1 mm Ø cables for 6.1 to 7.3 mm Ø cables for 7.3 to 8.4 mm Ø cables</p>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%;"></td> <td style="width:10%; text-align:center;">Det.</td> <td style="width:10%; text-align:center;">Name</td> <td rowspan="3" style="text-align:center;"> </td> <td rowspan="3" style="vertical-align: top;"> han IP67 Push-Pull Plug Shielded hybrid module , with 3 stamped Power contacts and 4 data contacts. </td> <td style="text-align:center;">Meßstab/ Scale</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align:center;">Detail.</td> <td style="text-align:center;">15-01-06</td> <td style="text-align:center;">JFB</td> <td style="text-align:center;">1.5</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align:center;">Insp.</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align:center;">Stand.</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>					Det.	Name		han IP67 Push-Pull Plug Shielded hybrid module , with 3 stamped Power contacts and 4 data contacts.	Meßstab/ Scale				Detail.	15-01-06	JFB	1.5				Insp.							Stand.					<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:10%; text-align:center;">34386</td> <td colspan="2" style="text-align:center;">HARTING EURL F-95972 Paris</td> <td rowspan="2" style="text-align:center;"> </td> <td style="text-align:center;">TB 09 45 145 1300</td> <td style="text-align:center;">Blatt/ Page 1 / 1</td> </tr> <tr> <td style="text-align:center;">Mod.</td> <td style="text-align:center;">Det.</td> <td style="text-align:center;">Name</td> <td style="text-align:center;">Sub. RP_090234_059</td> <td></td> </tr> </table>		34386	HARTING EURL F-95972 Paris			TB 09 45 145 1300	Blatt/ Page 1 / 1	Mod.	Det.	Name	Sub. RP_090234_059	
			Det.	Name		han IP67 Push-Pull Plug Shielded hybrid module , with 3 stamped Power contacts and 4 data contacts.	Meßstab/ Scale																																								
			Detail.	15-01-06			JFB	1.5																																							
			Insp.																																												
			Stand.																																												
34386	HARTING EURL F-95972 Paris			TB 09 45 145 1300	Blatt/ Page 1 / 1																																										
Mod.	Det.	Name		Sub. RP_090234_059																																											