

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Littelfuse](#)  
[59045-010](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)



**File E61760(N) 59045 and 59050 PCB Mount Features and Benefits**



**Features**

- 2 Part Magnetically Operated Proximity Sensor
- Standard normally open and high voltage normally open contact configuration
- Subminiature 17mm (0.700") version available Moulded stand-offs to allow board washing


**Benefits**

- Mounts directly into printed circuit board
- No standby power requirement
- Operates through non-ferrous materials such as wood, plastic or aluminium
- Hermetically sealed, magnetically operated contacts continue to operate long after optical and other technologies fail due to contamination
- Simple installation and adjustment

**Applications**

- Position and limit sensing
- Security system switch
- Door switch

**DIMENSIONS**



	A Max	B Max	C ± .10 (0,25)	D Max	E ± .015 (0,38)
<b>57045</b>	(.170) 4,32	(.700) 17,78	See Note Below	(.130) 3,3	—
<b>57050</b>	(.265) 6,73	(.900) 22,86	See Note Below	(.180) 4,57	—
<b>59045</b>	(.170) 4,32	(.700) 17,78	(.600) 15,24	(.130) 3,3	(.130) 3,30
<b>59050</b>	(.180) 4,57	(.900) 22,86	(.800) 20,32	(.170) 4,32	(.130) 3,30

Mounting: (.062) 1,57 thick board, (.125) 3,17 holes. **57045** on (.540) 13,72 and **57050** on (.720) 18,28 nom. centers.

**Recommended Activating Positions:**



Sensors and Matching Actuators (Note 2)		Actuator	Sensor	
Must Actuate	Must Release			
.075 (1,90)	.550 (13,97)	57045-000	59045-010	—
.150 (3,81)	.750 (19,05)	57050-000	59050-010	59050-020

Electrical Specifications and Operating Characteristics			Form A SPST-NO Standard	Form A SPST-NO High Voltage
Contact Rating		Watt - max.	10	10
Voltage	Switching	Vdc - max.	200	300
	Breakdown	Vdc - min.	250	450
Current	Switching	A - max.	0.5	0.5
	Carry	A - max.	1.0	1.5
Resistance	Contact, Initial	- max.	0.2	0.2
	Insulation	- min.	10 <sup>10</sup>	10 <sup>10</sup>
Capacitance	Contact	p F - typ.	0.3	0.2
Temperature	Operating	°C	-40 to + 105	-20 to + 105
	Storage	°C	-65 to + 105	-65 to + 105
Time	Operate	ms - typ.	1.0	1.0
	Release	ms - typ.	1.0	1.0
Shock	1 lms 1/2 sine	G - max.	100	100
Vibration	50-2000 Hz	G - max.	30	30

- Notes:
1. Board Mounting:  
**57045-000** requires (0.062) 1,57 thick board, (0.125) 3,17 dia. holes on (0.540) 13,72 nominal centers.  
**57050-000** requires (0.062) 1,57 thick board, (0.125) 3,17 dia. holes on (0.720) 18,28 nominal centers.
  2. Order Actuators as a separate item.
  3. Underwriters Laboratories recognition. For details on electrical specifications, contact Hamlin, Inc.

INFORMATION PROVIDED ON THIS DATA SHEET IS PROVIDED FOR INFORMATION PURPOSES ONLY AND SHOULD NOT BE RELIED UPON AS BEING ACCURATE FOR ANY PARTICULAR PURPOSE. Product performance may be affected by the application to which the product is put. Upon request, HAMLIN will assist purchasers by providing information specific to any particular application. HAMLIN disclaims any and all liability whatsoever for any purchaser's reliance upon the information contained on this data sheet without further consultation with authorised representatives of HAMLIN.