

Excellent Integrated System Limited

Stocking Distributor


Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Bel Fuse Inc.](#)
[VNS10-2051](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

RoHS COMPLIANT



For stripping and assembly instructions see Drawing Number: VAIN1205

Electrical Characteristics

Nominal Impedance:	50 ohms
Frequency Range:	DC to 11 GHz
VSWR:	1.35:1 maximum
Insertion Loss:	0.17 dB max
Operating Voltage (rms):	1500 V maximum at sea level
Dielectric Withstand Voltage (rms):	2500 V maximum at sea level
Contact Resistance:	1.0 milliohms maximum
Insulation Resistance:	5000 megohms minimum

Mechanical Characteristics

Mating Cycles:	500 cycles minimum
Interface Dimensions:	Conform to MIL-C-39012

Environmental Characteristics

Temperature Range:	-55 °C to +85 °C
--------------------	------------------

PART	DESCRIPTION
1	Clamp Nut Brass, nickel plated
2	Washer Steel, nickel plated
3	Gasket Rubber
4	Taper Clamp Brass, nickel plated
5	Body Brass, nickel plated
6	Dielectric Teflon
7	Contact Brass, gold plated

Strip Dimensions Updated	JC	5	06 April 11
Dimensions Updated	JT	4	04 Mar 10
Update Dims	MS	3	7 Jan 09
Amendment	BT	2	24 Sept 08
First Issue	BT	1	11 Nov 07
DESCRIPTION OF REVISION	APPVD	ISS	DATE



Cinch Connectivity Solutions
7-13 Russel Way,
Widford Industrial Estate,
Chelmsford, Essex,
CM1 3AA, UK.
Tel: +44 (0) 1245 359515
Fax: +44 (0) 1245 358938

SCALE: Not To Scale
DIMENSIONS: mm
TOLERANCES:
± 0.2mm unless
otherwise stated

DRAWN BY: B Thomas
CHECKED BY: M Spooner
APPROVED BY: M Spooner
DATE: 05 Nov 07

TITLE:
N Clamp Plug for RG58

PART NUMBER:
VNS10-2051
PAGE: 1 of 1