

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[117-00018](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

117-00018



**Article Number: 117-00018**

**Double Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 100/pkg**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 117-00018

**Type** T50SDH

**Color** Black (BK)

**Features and Benefits**

- Design allows the fastening of two separate bundles.
- The tie's second loop may can serve as a positioning device for a single bundle.

**Product Description** The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Double Head Tie, 50lb, 6.3" Length, 0.19" Width, PA66, Black, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225.0 N

**Length L (Imperial)** 6.3 "

**Length L (Metric)** 159.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Variant** Inside Serrated

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter 1st Loop Max. (Imperial)** 1.4 "

**Bundle Diameter 1st Loop Max. (Metric)** 35.0 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 5000

## Material and Specifications

**Material** Polyamide 6.6 (PA66)



**Material Shortcut** PA66

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes