

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[126-00046](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

126-00046



Article Number: 126-00046

Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66HS, Black, 1,000/pkg



Download drawing



Download spec sheet

## Base Data

Local Order Number 126-00046

Type T50SSF

Color Black (BK)

- Features and Benefits
- Quick and easy mounting will save time.
  - Tie is releasable and reusable providing a cost savings.
  - Design provides low insertion and high extraction force.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66HS, Black, 1,000/pkg

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.25 "

Length L (Metric) 159.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Height H (Imperial) 0.3 "

Height H (Metric) 7.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Panel Thickness Max. (Imperial) 0.14 "

Panel Thickness Max. (Metric) 3.56 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 1.0 mm

Mounting Hole Diameter D (Metric) 6.4 - 7.1 mm

Mounting Hole Diameter D (Imperial) 0.25 "

(Imperial) **Mounting Hole Diameter D Max.**0.28 "  
(Imperial)

**Mounting Hole Diameter D Max.**7.1 mm  
(Metric)6.4 mm

**Mounting Hole Diameter D Min. (Metric)**

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 1000

**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes