

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[150-95500](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

150-95500



Article Number: 150-95500

Tape Clip-Length 1.46" Pan Thickness .03"- .06" Mounting Hole Dia .26-.28" PA66HIRHS Black 1000/Pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 150-95500

Type TC5FT6S

Color Black (BK)

Features and Benefits Standard tape clips secure the bundle directly above the mounting hole.

Short Description Tape Clip-Length 1.46" Pan Thickness .03"- .06" Mounting Hole Dia .26-.28" PA66HIRHS Black 1000/Pkg

Product Dimensions

Length L (Imperial) 1.46 "

Length L (Metric) 37.0 mm

Fixation Method Fir Tree

Width W (Imperial) 0.32 "

Width W (Metric) 8.0 mm

Height H (Imperial) 0.32 "

Height H (Metric) 8.2 mm

Height H2 (Imperial) 0.2 "

Height H2 (Metric) 5.0 mm

Panel Thickness Max. (Imperial) 0.06 "

Panel Thickness Max. (Metric) 1.5 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.75 mm

Mounting Hole Diameter D (Metric) 6.4 - 7.1 mm

Mounting Hole Diameter D Min. (Imperial) 0.26 "

Mounting Hole Diameter D Max. 0.28 "

(Imperial)

Mounting Hole Diameter D Max. 7.1 mm

(Metric) 6.4 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 25000 Pieces

Weight (Metric) 0.55 kg



Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes