

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[151-00663](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

151-00663



Article Number: 151-00663

Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 5.7mm, PA66HIRHSUV, Black, 2000/box

 [Download drawing](#)

 [Download spec sheet](#)

Base Data

Local Order Number 151-00663

Type TC6FT6

Color Black (BK)

Features and Benefits

- Staggered fir tree branch design provides low insertion forces and high extraction forces for easy assembly.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Product Description HellermannTyton's Bundling Clip includes an extended fir tree mount to allow for a wide panel thickness range (0.7 - 18.0 mm). Anti-sliding bars on the ends of the connection bar assist in preventing the cable ties or tape from sliding off the clip in high movement/vibration applications.

Short Description Bundling Clip, Hole Diameter 6.2 - 6.8mm, Panel 0.7 - 5.7mm, PA66HIRHSUV, Black, 2000/box

Product Dimensions

Length L (Imperial) 1.5 "

Length L (Metric) 38.1 mm

Fixation Method Fir Tree

Width W (Imperial) 0.5 "

Width W (Metric) 12.0 mm

Height H (Imperial) 0.5 "

Height H (Metric) 14.0 mm

Height H2 (Imperial) 0.4 "

Height H2 (Metric) 10.5 mm

Panel Thickness Max. (Imperial) 0.71 "

Panel Thickness Max. (Metric) 5.7 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.7 mm

Mounting Hole Diameter D (Imperial) 0.26 "

Mounting Hole Diameter D (Metric) 6.5 mm

Mounting Hole Diameter D Min. (Imperial) 0.24 "

Mounting Hole Diameter D Max. (Imperial) 0.27 "

Mounting Hole Diameter D Max. (Metric) 6.8 mm

Mounting Hole Diameter D Min. (Metric) 6.2 mm

Logistics and Packaging

Quantity Per box

Carton Quantity 2000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)