Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton
156-00017

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

156-00017

Article Number: 156-00017

Cable Tie and Edge Clip, 50 lb, 6.0" Long, EC21, Panel Thickness .04"-.12", PA66HS, Black, 500/bag

RoHS

Download drawing Download spec sheet

Base Data

Local Order Number	156-00017
Type	T50SOSEC21
Color	Black (BK)
Features and Benefits	• Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. • Two piece assembly allows the mount to slide along the strap ensuring proper orientation. • Cable tie is outside serrated to reduce bundle chafing.
Product Description	The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.
Short Description	Cable Tie and Edge Clip, 50 lb, 6.0" Long, EC21, Panel Thickness .04"-.12", PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial)	50.0 lbs
Minimum Tensile Strength (Metric)	225 N
Length L (Imperial)	6.0 "
Length L (Metric)	150 mm
Length L2 (Imperial)	0.6 "
Length L2 (Metric)	15.0 mm
Fixation Method	EdgeClip, sideway, assembled, 2 piece
Identification Plate Position	none
Releasable Closure	No
Variant	Outside Serrated
Width W (Imperial)	0.18 "
Width W (Metric)	4.6 mm
Width W2 (Imperial)	0.4 "
Width W2 (Metric)	10.0 mm
Height H (Imperial)	0.05 "
Height H (Metric)	1.3 mm
Height H2 (Imperial)	0.53 "
Height H2 (Metric)	13.4 mm
Bundle Diameter Min. (Imperial)	0.04 "
Bundle Diameter Min. (Metric)	1.0 mm
Bundle Diameter Max. (Imperial)	1.4 "

Bundle Diameter Max. (Metric)	35.0 mm
Panel Thickness Max. (Imperial)	0.12 "
Panel Thickness Max. (Metric)	3.0 mm
Panel Thickness Min. (Imperial)	0.04 "
Panel Thickness Min. (Metric)	1.0 mm
Thickness T (Imperial)	0.05 "
Thickness T (Metric)	1.3 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500 Pieces
Carton Quantity	4000 Pieces
Weight (Metric)	1.9 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes

© HellermannTyton 2015