



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 156-00591 - CABLE TIE/EDGE CLIP 50LB 7.9"

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[156-00591](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

156-00591



Article Number: 156-00591

Cable Tie and Edge Clip, 50lb, 8.0" Long, EC20, Panel Thickness .12"-.24", PA66UV, Black, 100/bag



Download spec sheet

## Base Data

Local Order Number 156-00591

Type T50REC20

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
  - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
  - Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

**Product Description** This cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

**Short Description** Cable Tie and Edge Clip, 50lb, 8.0" Long, EC20, Panel Thickness .12"-.24", PA66UV, Black, 100/bag

## Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Length L (Imperial) 8.0 "

Length L (Metric) 200 mm

Length L2 (Imperial) 0.58 "

Length L2 (Metric) 14.8 mm

Fixation Method EdgeClip, top, assembled, 2 piece

Identification Plate Position none

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Width W2 (Imperial) 0.55 "

Width W2 (Metric) 14.0 mm

Height H (Imperial) 0.05 "

Height H (Metric) 1.2 mm

Height H2 (Imperial) 0.7 "

Height H2 (Metric) 17.8 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 45.0 mm

Panel Thickness Max. (Imperial) 0.24 "

**Panel Thickness Min. (Imperial)** 0.12 "

**Panel Thickness Min. (Metric)** 3.00 mm

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 100

## Material and Specifications

---

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)  
Polyamide 6.6 UV-stabilized (PA66UV)

**Material Shortcut** PA66UV  
PA66HIRHSUV

**Material Cable Tie** Polyamide 6.6 UV-stabilized (PA66UV)

**Flammability** UL94 V2  
UL94 HB

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)  
-40°F to +230°F (-40°C to +110°C)

**ROHS Compliant** Yes