



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 157-00402 - WDE TIE W/1/4" STD 120LB 15.7"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[157-00402](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

157-00402



Article Number: 157-00402

Wide Strap Cable Tie, 1/4" Stud Mount, 15.7" Length, 0.5" Wide, PA66HIRHSUV, Black, 300/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00402

Type WSR250

Color Black (BK)

- Features and Benefits**
- Mount provides low insertion and high extraction forces which makes for a strong and easy installation.
 - Clamping rails increase grip on round bundles.
 - Thinner strap provides increased flexibility for improved ergonomics.
 - Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

Product Description Wide Strap Heavy Duty Cable Ties features a stud mount for direction application onto a 1/4" threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 4.2". The low profile mount design engages a minimum of 4 threads on the stud which makes it easier to apply additional mounts onto one stud.

Short Description Wide Strap Cable Tie, 1/4" Stud Mount, 15.7" Length, 0.5" Wide, PA66HIRHSUV, Black, 300/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 15.7 "

Length L (Metric) 389.0 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.38 "

Bundle Diameter Min. (Metric) 10.0 mm

Bundle Diameter Max. (Imperial) 4.1 "

Bundle Diameter Max. (Metric) 104.0 mm

Stud Size (Imperial) 0.25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 300 Pieces



Carton Quantity 1200 Pieces

Material and Specifications

| | |
|------------------------------|--|
| Material | Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HIRHSUV |
| Flammability | UL94 HB |
| Operating Temperature | -65°F to +212°F (-54°C to +100°C) |
| ROHS Compliant | Yes |