



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[170-03008](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03008



**Article Number: 170-03008**

**Flame Retardant Expandable Braided Sleeving, 0.75" Dia., Black, 75.0 ft/Standard Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03008

**Type** BSPFR340

**Color** Black (BK)

**Features and Benefits**

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

**Product Description** A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

**Short Description** Flame Retardant Expandable Braided Sleeving, 0.75" Dia., Black, 75.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 75.0 ft

**Length L (Metric)** 22.9 m

**Reel Length (imperial)** 75.0 ft

**Bundle Diameter Min. (Imperial)** 0.5 "

**Bundle Diameter Min. (Metric)** 12.7 mm

**Bundle Diameter Max. (Imperial)** 1.25 "

**Bundle Diameter Max. (Metric)** 31.8 mm

**Nominal Diameter (Imperial)** 3/4 "

**Nominal Diameter (Metric)** 19.1 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 75 ft

**Weight (imperial)** 0.65 lbs

**Weight (Metric)** 0.30 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** Mil-202  
 FMVSS 302  
 FAR 25



VW-1

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes