



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03018 - 3/4" FRAY RES FR BRDD SLVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03018](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03018



Article Number: 170-03018

Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.75" Dia., Black, 75.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03018

Type BSSCFR340

Color Black (BK)

- Features and Benefits**
- Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.
 - Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.
 - Cuts with ordinary scissors without fraying ends.

Product Description Treated polyester yarns that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.

Short Description Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.75" Dia., Black, 75.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 75.0 ft

Length L (Metric) 22.9 m

Reel Length (imperial) 75.0 ft

Bundle Diameter Min. (Imperial) 0.625 "

Bundle Diameter Min. (Metric) 15.9 mm

Bundle Diameter Max. (Imperial) 1.0 "

Bundle Diameter Max. (Metric) 25.4 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 75 ft

Weight (Metric) 0.38 kg

Weight (imperial) 0.83 lbs

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL VW-1
Mil-202

Operating Temperature -94°F to +257°F (-70°C to +125°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03018 - 3/4" FRAY RES FR BRDD SLVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes

UL Recognized (US and Canada) Yes