

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[170-03021](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03021



**Article Number: 170-03021**

**Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.5" Dia., Black, 50.0 ft/Standard Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03021

**Type** BSSCFR1120

**Color** Black (BK)

**Features and Benefits**

- Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.
- Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.
- Cuts with ordinary scissors without fraying ends.

**Product Description** Treated polyester yarns that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.

**Short Description** Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.5" Dia., Black, 50.0 ft/Standard Reel

## Product Dimensions

**Length L (Imperial)** 50.0 ft

**Length L (Metric)** 15.2 m

**Reel Length (imperial)** 50.0 ft

**Bundle Diameter Min. (Imperial)** 1.25 "

**Bundle Diameter Min. (Metric)** 31.8 mm

**Bundle Diameter Max. (Imperial)** 2.0 "

**Bundle Diameter Max. (Metric)** 50.8 mm

**Nominal Diameter (Imperial)** 1-1/2 "

**Nominal Diameter (Metric)** 38.1 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 50 ft

**Weight (imperial)** 0.93 lbs

**Weight (Metric)** 0.42 kg

## Material and Specifications

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL VW-1  
Mil-202

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03021 - 1-1/2" FRAY RES FR BRDD SLVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes