



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03041 - 1/4" PET BRAIDED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03041](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03041



Article Number: 170-03041

Expandable Braided Sleeve, 0.25" Dia., Black, 1000.0 ft/Bulk Reel



Download drawing



Download spec sheet

## Base Data

Local Order Number 170-03041

Type BSP140B

Color Black (BK)

- Features and Benefits**
- Weave construction adjusts to twisting and flexing without creating wrinkles or bends.
  - Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.
  - Color options available to provide easy visual and safety identification of critical wiring components.
  - Expands to 150% of nominal diameter for fast, easy installation.

**Product Description** General purpose expandable braided sleeve provides flexible abrasion protection for wire bundles and hoses.

**Short Description** Expandable Braided Sleeve, 0.25" Dia., Black, 1000.0 ft/Bulk Reel

## Product Dimensions

Length L (Imperial) 1000.0 ft

Length L (Metric) 304.8 m

Reel Length (imperial) 1000.0 ft

Bundle Diameter Min. (Imperial) 0.125 "

Bundle Diameter Min. (Metric) 3.2 mm

Bundle Diameter Max. (Imperial) 0.437 "

Bundle Diameter Max. (Metric) 11.1 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.4 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 1000 ft

Weight (Metric) 1.18 kg

Weight (imperial) 2.6 lbs

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability FAR 25  
FMVSS 302  
UL94 V0



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03041 - 1/4" PET BRAIDED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes